

AD 671933

AFCRL-68-0153
APRIL 1968
ENVIRONMENTAL RESEARCH PAPERS, NO. 285




AIR FORCE CAMBRIDGE RESEARCH LABORATORIES

L. G. HANSCOM FIELD, BEDFORD, MASSACHUSETTS

UV, Visible, and IR Attenuation for Altitudes to 50 km, 1968

L. ELTERMAN

OFFICE OF AEROSPACE RESEARCH
United States Air Force



AFCRL-68-0153
APRIL 1968
ENVIRONMENTAL RESEARCH PAPERS, NO. 285

OPTICAL PHYSICS LABORATORY PROJECT 7670

AIR FORCE CAMBRIDGE RESEARCH LABORATORIES

L. G. HANSCOM FIELD, BEDFORD, MASSACHUSETTS

**UV, Visible, and IR Attenuation
for Altitudes to 50 km, 1968**

L. ELTERMAN

Distribution of this document is unlimited. It may
be released to the Clearinghouse, Department of
Commerce, for sale to the general public.

OFFICE OF AEROSPACE RESEARCH
United States Air Force



Abstract

An atmospheric attenuation model for the ultraviolet, visible, and infrared was developed in 1964, based on scattering (molecules and aerosols) and ozone absorption. Since then more measurements have been made and our knowledge of aerosol attenuation has widened. These circumstances result in attenuation model changes which are relatively unimportant for most exploratory calculations. They can be significant, however, for long slant-path high-altitude applications entailing large zenith angles, factors which characterize, for example, the measurement geometries of rockets and satellites. Accordingly, a revision of the 1964 Attenuation Model is warranted.

In this paper the optical parameters are computed spectrally and with altitude as follows: (1) pure air attenuation parameters are determined by utilizing Rayleigh scattering cross sections with molecular number densities from the standard atmosphere; (2) ozone absorption parameters are derived based on Vigroux's coefficients applied to a representative atmospheric ozone distribution; (3) seven sets of aerosol measurements are compared and a profile of aerosol attenuation coefficients vs altitude is developed. Attenuation coefficients and optical thickness due to molecular, aerosol, and ozone attenuation are computed and tabulated individually so that the influence of each can be compared. The newly derived tabulations permit various exploratory calculations, including horizontal, vertical, and slant-path transmission at kilometer intervals to an altitude of 50 km, individually for each attenuating component or for overall atmospheric extinction (molecular + ozone + aerosol).

Contents

1. INTRODUCTION	1
2. RAYLEIGH PARAMETERS	3
3. ABSORPTION PARAMETERS FOR ATMOSPHERIC OZONE	7
4. AEROSOL ATTENUATION	8
5. ATMOSPHERIC EXTINCTION	20
6. EXPLORATORY TRANSMISSION CALCULATIONS	20
7. CONCLUDING REMARKS	21
8. TABULATION OF PARAMETERS	21
ACKNOWLEDGMENTS	45
REFERENCES	47

Illustrations

1. Index of Refraction for 1013 mb and 15°C (Table 1)	4
2. Rayleigh Cross Section vs Wavelength (Table 1)	4
3. Representative Atmospheric Ozone Concentration Profile (Table 2)	7
4. Aerosol Attenuation Coefficients vs Altitude at $\lambda_1 = 0.55\mu$	9

Illustrations

5. Single Profile $\beta_p(h, \lambda_1)$ for 11 April 1964 at 02:00 MST, Similar to Mean of 79 Profiles	11
6. Single Turbidity Profile $\beta_p(h, \lambda_1)/\beta_r(h, \lambda_1)$ for 11 April at 02:00 MST	12
7. Mean of 79 Low Stratospheric Dust Profiles (Table 3) for April 1964 to April 1965	14
8. Mean Turbidity Profile $\beta_p(h, \lambda_1)/\beta_r(h, \lambda_1)$	15
9. Expanded Scale for 26 to 32 km Altitude Region Showing $H_p = 3.75$ km for 79 Profile Mean	16
10. Comparison of Profiles	17
11. Aerosol Attenuation Coefficients $\beta_p(0, \lambda)$ vs Wavelength at Sea Level for a Meteorological Range Approximating 25 km	19

Tables

1. Model Parameters as a Function of Wavelength	2
2. Model Parameters as a Function of Altitude	6
3. Aerosol Optical Thickness as a Measure of Volcanic Dust, $\lambda_1 = 0.55\mu$	13
4. Parameters at 0.27μ to 4.00μ (Tables 4.1 to 4.22)	22

Symbols

A_v	Vigroux ozone absorption coefficient (cm^{-1})
D_3	Ozone concentration (cm/km)
d	Horizontal path length (km)
H_p	Aerosol scale height (km)
h	Altitude (km)
K	Mie scattering efficiency
m	Aerosol index of refraction
m_s	Index of refraction at sea level, air at 1013 mb and 15°C
N_3	Ozone number density (cm^{-3})
N_p	Aerosol number density (cm^{-3})
N_r	Molecular number density (cm^{-3})
N_s	Molecular number density at sea level (cm^{-3})
r	Particle radius (microns)
t_p	Turbidity (β_p/β_r)
T	Temperature °K
T_h	Horizontal transmission
T_{0-h}	Transmission between sea level and altitude h
$T_{h-\infty}$	Transmission between h and space
$T_{\Delta h}$	Transmission between two altitudes above sea level
β_3	Atmospheric ozone absorption coefficient (km^{-1})
β_p	Aerosol attenuation coefficient (km^{-1})
$\bar{\beta}_p(h, \lambda_1)$	Mean of 79 profiles for $\lambda_1 = 0.55$ microns (km^{-1})

β_r	Rayleigh attenuation coefficient (km^{-1})
β_{ext}	Extinction coefficient (km^{-1})
δ	Depolarization factor
θ	Zenith angle
λ	Wavelength (microns or cm)
λ_1	Wavelength 0.55 microns
σ_r	Rayleigh scattering cross section (cm^2)
τ_3	Ozone optical thickness from sea level to altitude h (0-h)
τ_3'	Ozone optical thickness from altitude h to space ($h-\infty$)
τ_p	Aerosol optical thickness from sea level to altitude h, (0-h)
τ_p'	Aerosol optical thickness from altitude h to space, ($h-\infty$)
τ_r	Rayleigh optical thickness from sea level to altitude h, (0-h)
τ_r'	Rayleigh optical thickness from altitude h to space, ($h-\infty$)
τ_{ext}	Extinction optical thickness (molecular + ozone + aerosol) from sea level to altitude h, (0-h)
τ_{ext}'	Extinction optical thickness (molecular + ozone + aerosol) from altitude h to infinity, ($h-\infty$)
ψ	Aerosol size distribution function

UV, Visible, and IR Attenuation for Altitudes to 50 km, 1968*

1. INTRODUCTION

In 1964, an atmospheric attenuation model was published (Elterman, 1964) which has been useful for a variety of exploratory calculations. Now a revision is warranted for reasons given in the abstract and Section 4 of this report. In this revision most of the earlier material is presented in summary form. The section on attenuation by Rayleigh scattering, however, is retained because the content leading to the derivation of the Rayleigh parameters is useful. In one instance, due to existing interest, the material is expanded, i.e., the tabulations which comprise the attenuation model now include aerosol and ozone optical thickness so that a comparison can be made of the relative importance of each attenuating component for vertical and slant paths.

The shortest wavelength considered is 0.27 microns. The use of shorter wavelengths would require a treatment of O_2 absorption. Also, attenuation is sufficiently severe so that interest in the shorter wavelength region for purposes of ultraviolet transmission below 50 km probably is limited. The longest wavelength used is 4.0 microns. Calculations for longer wavelengths are complicated by the presence of absorption bands of H_2O , CO_2 , and their wings. In between, a total of 22 wavelengths is chosen (Table 1) within the atmospheric windows and for the ultraviolet region where ozone absorption is important.

(Received for publication 25 March 1968)

Conceptually, the attenuation model starts with molecular densities from the latest published U.S. Standard Atmosphere (1962) followed by the addition of ozone and aerosol components. The meteorological range (M.R.) at sea level corresponds to about 25 km at 0.55μ wavelength. This choice serves a useful function because it permits including some important measurements conducted at $\lambda = 0.55\mu$. In addition, this wavelength customarily represents the photopic region.

Table 1. Model Parameters as a Function of Wavelength

λ (microns)	m_s	σ_r (cm ²)	A_v (cm ⁻¹)
0.27	1.00029668	8.960×10^{-26}	2.10×10^2
0.28	1.00029475	7.646×10^{-26}	1.06×10^2
0.30	1.00029156	5.677×10^{-26}	1.01×10^1
0.32	1.00028902	4.310×10^{-26}	8.98×10^{-1}
0.34	1.00028699	3.334×10^{-26}	6.40×10^{-2}
0.36	1.00028531	2.622×10^{-26}	1.80×10^{-3}
0.38	1.00028392	2.091×10^{-26}	0
0.40	1.00028275	1.689×10^{-26}	0
0.45	1.00028052	1.038×10^{-26}	3.50×10^{-3}
0.50	1.00027896	6.735×10^{-27}	3.45×10^{-2}
0.55	1.00027782	4.563×10^{-27}	9.20×10^{-2}
0.60	1.00027697	3.202×10^{-27}	1.32×10^{-1}
0.65	1.00027630	2.314×10^{-27}	6.20×10^{-2}
0.70	1.00027578	1.714×10^{-27}	2.30×10^{-2}
0.80	1.00027503	9.990×10^{-28}	1.00×10^{-2}
0.90	1.00027451	6.213×10^{-28}	0
1.06	1.00027397	3.216×10^{-28}	0
1.26	1.00027357	1.606×10^{-28}	0
1.67	1.00027315	5.189×10^{-29}	0
2.17	1.00027292	1.817×10^{-29}	0
3.50	1.00027272	2.681×10^{-30}	0
4.00	1.00027269	1.571×10^{-30}	0

λ - Wavelength

m_s - Index of refraction (1013 mb, 15°C)

σ_r - Rayleigh scattering cross section

A_v - Absorption coefficient after Vigroux for pure O₃, smoothed values (1013 mb, 18°C)

2. RAYLEIGH PARAMETERS

A fundamental requirement for generating an accurate series of Rayleigh parameters is an exact determination of the index of refraction for the wavelengths of interest. With this known, the Rayleigh cross sections can be computed. This in turn permits computation of the Rayleigh attenuation coefficient and its variation with altitude as well as corresponding optical thickness values.

The index of refraction for a standard atmosphere (1013 mb, 15°C) specifically for the desired wavelengths used is determined by Edlen's (1953) expression

$$(m_s - 1)10^{-8} = 6432.8 + \frac{2949810}{146 - (\lambda^{-2})} + \frac{25540}{41 - (\lambda^{-2})} \quad (1)$$

where m_s = refractive index,
 λ = wavelength (microns).

Penndorf's (1957) computations using Eq. (1) demonstrate that the effect of water vapor can be neglected and the derived m_s values have negligible error for the spectral range from 0.2 to 20.0 microns.

The Rayleigh cross section is expressed by

$$\sigma_r(\lambda) = \frac{8\pi^3(m_s^2 - 1)^2}{3\lambda^4 N_s^2} \cdot \frac{6 + 3\delta}{6 - 7\delta} \quad (2)$$

where

- σ_r = the Rayleigh scattering cross section (cm^2),
- λ = the wavelength (cm),
- m_s = the index of refraction of air at 15°C and 1013 mb pressure,
- N_s = the molecular number density at sea level for a standard atmosphere (cm^{-3}),
- δ = the depolarization factor.

The term $(6 + 3\delta)/(6 - 7\delta)$ accounts for the degree of depolarization attributable to the anisotropy of the atmospheric molecule. The depolarization factor has been determined by calculation and by laboratory measurement. The latest work of Gucker and Basu (1953) yields $\delta = 0.035$. The wavelengths of interest with the indices of refraction and Rayleigh cross sections [computed from Eqs. (1) and (2)] are listed in Table 1, and plotted in Figures 1 and 2.

Using the scattering cross sections, the Rayleigh coefficients are obtained with




Figure 1. Index of Refraction for 1013 mb and 15°C (Table 1),
 ooooo Represent Attenuation Model Wavelengths




Figure 2. Rayleigh Cross Section vs Wavelength (Table 1),
 ooooo Represent Attenuation Model Wavelengths

$$\beta_r(h, \lambda) = \sigma_r(\lambda) \cdot N_r(h) \cdot (10^3 \text{ cm/km}) \quad (3)$$

where

- β_r = the Rayleigh attenuation coefficient (km^{-1}),
- σ_r = the Rayleigh scattering cross section (cm^2),
- N_r = the molecular number density (cm^{-3}).

The values of $N_r(h)$ needed for Eq. (3) were obtained from the U.S. Standard Atmosphere and are listed in Table 2. This expression is used to compute an array of Rayleigh attenuation coefficients as a function of altitude for each wavelength.

With the Rayleigh attenuation coefficients determined, the optical thicknesses from sea level to some altitude h are computed by

$$\tau_r(h, \lambda) = \sum_0^h \bar{\beta}_r(h, \lambda) \Delta h \quad (4)$$

where

- τ_r = Rayleigh optical thickness (0 - h),
- $\bar{\beta}_r$ = mean of the Rayleigh attenuation coefficients (km^{-1}) for each altitude increment,
- Δh = altitude increment chosen as one km for these calculations.

The Rayleigh optical thickness for altitude h to space is obtained by the relationship

$$\tau_r^1(h, \lambda) = \tau_r(\infty, \lambda) - \tau_r(h, \lambda) \quad (5)$$

where

- $\tau_r^1(h)$ = Rayleigh optical thickness ($h - \infty$),
- $\tau_r(\infty)$ = Rayleigh optical thickness (0 - ∞).

The term $\tau_r(\infty)$ was obtained by using Eq. (4) with the limits set between 0 and 80 km. Above 80 km, Stergis' (1966) calculations, based on N_2 , O_2 , and O as the principal atmospheric constituents, yield

$$\int_{80}^{\infty} \beta_r(h, \lambda) dh = \begin{cases} 3.6 \times 10^{-6}, & \lambda = 0.4 \mu \\ 6.7 \times 10^{-7}, & \lambda = 0.6 \mu \\ 2.1 \times 10^{-7}, & \lambda = 0.8 \mu \end{cases}$$

These values approximate a constant 10^{-5} , that of the Rayleigh optical thickness for unity air mass. For our purposes then the integral can be neglected because the constant is small and applies to all wavelengths of interest.

Table 2. Model Parameters as a Function of Altitude

h (km)	N_r (cm ⁻³)	D_3 (cm/km)
0	2.547×10^{19}	3.56×10^{-3}
1	2.311	3.26
2	2.093	2.93
3	1.891	2.50
4	1.704	2.26
5	1.531	2.21
6	1.373	2.16
7	1.227	2.23
8	1.093	2.28
9	9.712×10^{18}	2.81
10	8.598	3.50
11	7.585	4.60
12	6.486	6.21
13	5.543	8.45
14	4.738	9.57
15	4.049	9.94
16	3.461	1.03×10^{-2}
17	2.959	1.11
18	2.529	1.22
19	2.162	1.42
20	1.849	1.64
21	1.574	1.84
22	1.341	1.97
23	1.144	1.98
24	9.760×10^{17}	1.93
25	8.335	1.80
26	7.123	1.63
27	6.092	1.41
28	5.214	1.23
29	4.466	1.07
30	3.828	9.03×10^{-3}
31	3.283	7.93
32	2.818	6.82
33	2.406	5.82
34	2.056	4.85
35	1.760	4.31
36	1.509	3.61
37	1.296	3.02
38	1.116	2.53
39	9.620×10^{16}	2.17
40	8.308	1.86
41	7.187	1.52
42	6.227	1.19
43	5.404	9.30×10^{-4}
44	4.697	7.44
45	4.088	5.76
46	3.564	4.46
47	3.112	3.53
48	2.738	2.79
49	2.418	2.23
50	2.135	1.86

h - Altitude; N_r - Molecular number density;
 D_3 - Ozone equivalent thickness

3. ABSORPTION PARAMETERS FOR ATMOSPHERIC OZONE

This section is a summary of the material used in the 1964 Attenuation Model.

The parameter for determining O_3 absorption as a function of altitude is the atmospheric ozone absorption coefficient expressed by:

$$\beta_3(h, \lambda) = A_v(\lambda) D_3(h) \quad (6)$$

β_3 = atmospheric ozone absorption coefficient (km^{-1}),

A_v = the pure ozone absorption coefficient (cm^{-1}) after Vigroux,

D_3 = the ozone equivalent thickness (cm/km).

Thus, the Vigroux coefficients (1953) listed in Table 1 in conjunction with the ozone concentrations, Table 2 and Figure 3, permit the computation of an array of atmospheric ozone absorption coefficients to 50 km for each of the desired wavelengths.




Figure 3. Representative Atmospheric Ozone Concentration Profile (Table 2). Values for: 0 to 30 km, based on Handbook of Geophysics and Space Environment (1965) 30 to 40 km, interpolated 40 to 50 km, based on London, Ooyama, and Prabhakara (1962)

The ozone optical thickness from sea level to altitude h , $\tau_3(h, \lambda)$, and the ozone optical thickness from some altitude h to space, $\tau'_3(h, \lambda)$, are included in the model tabulations. The expressions for deriving these parameters have the same form as Eqs. (4) and (5).

4. AEROSOL ATTENUATION

Of the various methods used to investigate aerosol attenuation, for the present we will consider optical techniques only because they are suited to this type of study. In this country, Newkirk and Eddy (1964) used solar aureole photometry; Penndorf (1954) analyzed solar radiation measurements from aircraft altitudes; Elterman's results (1966a, b), with searchlight probing, comprise a substantial number of profiles acquired in New Mexico for altitudes to about 34 km. In Australia, Crosby and Koerber (1962) used a balloon-borne integrating nephelometer. In the U.S.S.R., Kondratiev, et al. (1967), conducted balloon solar transmission measurements; Feoktistov (1965) analyzed photographs of the earth's horizon from the spacecraft Voschod; Rozenberg, et al. (1960) (1966), acquired their results with searchlight probing. The various results, as shown in Figure 4, were made comparable at $\lambda_1 = 0.55\mu$ by using the empirical relationship that the aerosol attenuation coefficient is inversely proportional to wavelength. For reasons of clarity, a substantial body of results was not included in Figure 4, as for example the twilight measurements by Rozenberg (1966), Volz and Goody (1962), the searchlight measurements by Spankuch (1967), analysis of twilight aureole photographs from the spacecraft Vostok-6 by Draving (1966), the aircraft measurements of sky brightness by Sandomirski, Al'tovskaia and Trifonova (1964), and aircraft nephelometry by Waldram (1945). Also, interesting results in the form of relative values have been obtained with optical techniques: the twilight measurements by Bigg (1964), the laser beam backscatter by Collis and Ligda (1966), by Clemeshaw, Kent, and Wright (1967), and by Grams and Fiocco (1967).

A consideration of all results shows, as does Figure 4, that the aerosol attenuation coefficient is a strongly fluctuating parameter and that average values based on an adequate number of measurements are necessary in order to establish a representative profile. The recent searchlight probing measurements (Elterman, 1966a and 1966b) appear representative based on several considerations. First, each profile was acquired by continuous measurement through both troposphere and stratosphere and with an altitude resolution approximating one km. In addition, a total of 119 profiles comprising absolute values of aerosol attenuation coefficients were determined for various times throughout the year. This represents a substantially larger sample than previously published. Further, such a quantity of




Figure 4. Aerosol Attenuation Coefficients vs Altitude at $\lambda_1 = 0.55\mu$.
Comparison of results:

- XXXX solar aureole, 2 balloon flights, Newkirk and Eddy (1964);
- ΔΔΔΔ solar radiation measured from aircraft, mean of 8 flights, Penndorf (1954);
- ++++ searchlight probing, mean of 105 profiles, Elterman (1966a) and (1966b);
- o o o o balloon integrating nephelometer, mean of 14 flights, Crosby and Koerber (1962);
- • • • solar radiation measured from balloons, mean of 3 flights, Kondratiev et al. (1967);
- ▲▲▲▲ spacecraft horizon photography, analysis of 4 frames, Rozenberg (1966), Feoktistov (1965);
- ○ ○ ○ searchlight probing, mean for 5 nights, Rozenberg (1966)

results readily permits statistical treatment. Finally, we note that the mean of the 119 profiles falls reasonably well within the values determined by other researchers, a circumstance which tends to provide a measure of comfort.

In considering the suitability of the 119 profiles, extensive averaging is required and this tends to wash out features easily noted in the individual profile. We present, therefore, in Figure 5 a single profile, chosen because its properties are readily evident and also because it is similar to the overall average. The features can be made to emerge more prominently if the aerosol coefficients are used to compute a turbidity profile, $t_p(h, \lambda_1) = \beta_p(h, \lambda_1) / \beta_r(h, \lambda_1)$, where β_p and β_r are the aerosol and Rayleigh coefficients respectively and $\lambda_1 = 0.55\mu$ (Figure 6).

Since volcanic dust in the atmosphere can have a residence time of several years, the effects of the Mt. Agung eruption (March 1963) must be considered. The direct measurements of Junge, Chagnon, and Manson (1961), Friend (1965), Mossop (1964), and Rosen (1968), collectively considered, before and after this event, show evidence of change in the stratospheric aerosol content. The observations of the twilight sky by Volz (1965) and Meinel and Meinel (1964) also show augmentation of stratospheric particulates. Since the searchlight probing measurements yielded absolute values of aerosol attenuation coefficients, the most suitable parameter to use for examining this feature quantitatively is the stratospheric aerosol optical thickness for the altitude region between the tropopause and 25 km. The reason for choosing the latter altitude limit will be discussed later. Accordingly, all profiles were placed in time-sequential groups determined by the similarity of the stratospheric dust feature. Then the optical thickness was computed by

$$\tau = \frac{1}{n} \sum_{i=1}^n \sum_{h_1}^{h_2} \bar{\beta}'(h) \Delta h, \quad (7)$$

where n is the number of profiles in the group, h_1 is the altitude of the tropopause, h_2 the 25 km altitude, $\bar{\beta}'$ the mean aerosol attenuation coefficient (within each profile) for the altitude interval, and Δh the altitude intervals used for computing the profiles. The results of this computation are presented in Table 3. The tabulation demonstrates a relatively high level of stratospheric dust for the December 1963 to March 1964 period. Beginning with April 1964, dust abatement and a generally stabilized level are in evidence. The mean optical thickness of Group (B+C+D) is 26 percent less than that of Group A. Since Group A entails a period of abnormally high aerosol content, its profiles are not representative. These results are in satisfactory agreement with the findings from the direct measurements of the authors mentioned.




Figure 5. Single Profile $\beta_p(h, \lambda_1)$ for 11 April 1964 at 02:00 MST,
 Similar to Mean of 79 Profiles, $\lambda_1 = 0.55 \mu$.
 Surface to 5 km - convective region;
 5 to 11.7 km - troposphere dust layer;
 11.7 to 23.8 km - stratosphere dust layer;
 25.6 km - upper altitude maximum
 + + + + aerosol (measurements)
 — molecular (computed)




Figure 6. Single Turbidity Profile $\beta_p(h, \lambda_1)/\beta_r(h, \lambda_1)$
for 11 April at 0200 MST.
+++++ Measurements
(See caption pertaining to Figure 5)

Table 3. Aerosol Optical Thickness as a Measure of Volcanic Dust, $\lambda_1 = 0.55\mu$

Group	Period (Inclusive)	Number of Profiles	Mean Optical Thickness (approx. 12-25 km)
A	Dec 1963 - Mar 1964	40	3.1×10^{-2}
B	Apr 1964 - Sep 1964	50	2.2
C	Oct 1964 - Nov 1964	10	2.7
D	Dec 1964 - Apr 1965	19	2.4
B+C+D	Apr 1964 - Apr 1965	79	2.3

The considerations discussed above justify the selection of the Group (B+C+D) profiles as a basis for developing representative aerosol attenuation parameters. It will be convenient to designate the 79 profile average for $\lambda_1 = 0.55\mu$ as $\bar{\beta}_p(h, \lambda_1)$ (Figure 7). This profile can be extended to encompass a larger altitude range by using the scale height relationship,

$$\bar{\beta}_p(h_2, \lambda_1) = \bar{\beta}_p(h_1, \lambda_1) \exp \left[- \frac{(h_2 - h_1)}{H_p} \right] \quad (8)$$

Penndorf's study (1954) shows that for the lowest 5 km, the aerosol coefficients fall off exponentially with a scale height $0.97 < H_p < 1.4$ km. We resort to the use of his mean value, $H_p = 1.2$ km, to extend the $\bar{\beta}_p(h, \lambda_1)$ profile from 3.7 km to sea level. This results in aerosol coefficients which are identical to those of the 1964 Attenuation Model for altitudes 0 to 3 km (Table 4.11).

Above the convective region, up to the tropopause the aerosol coefficients show a moderate gradient which is in close agreement with Penndorf's analysis (1954) of the vertical distribution of aerosols in the troposphere. Also, this section of the profile is based on high signal to noise measurements and extensive averaging, factors which contribute to its reliability. Additionally, this altitude region, being above the convective layer, is characterized by aerosol conditions which tend to be independent of surface terrain. These considerations suggest that the shape and values of the $\bar{\beta}_p(h, \lambda_1)$ profile for this altitude region are realistic.

Above the tropopause, up to 25 km, the coefficients are larger than those derived for the 1964 Attenuation Model by a factor of about 20 (at 20 km for $\lambda_1 = 0.55\mu$). This difference may be attributed in part to the intrinsic difficulties of converting a size distribution to an optical parameter, that is, establishing the radii limits, particle shape, chemistry, and index of refraction. Relative to profile shape, a turbidity maximum dominates at about 19 km (Figure 8). The measurements of Rosen (1968) and those of Volz (1968) for 1964 to 1968 are in satisfactory agreement




Figure 7. Mean of 79 Low Stratospheric Dust Profiles (Table 3) for April 1964 to April 1965. Aerosol attenuation coefficients, $\beta_p(h, \lambda_1)$; standard deviation limits attributable to error and atmospheric variations; $\lambda_1 = 0.55\mu$; ++++ measurements with searchlight probing




Figure 8. Mean Turbidity Profile, $\bar{\beta}_p(h, \lambda_1)/\beta_r(h, \lambda_1)$
(See caption for Figure 7)

with the mean optical thickness and shape of the Group (B+C+D) profiles, Table 3. Also their results show that the stratospheric dust level has remained approximately constant from 1964 to the time of this writing. The $\bar{\beta}_p(h, \lambda_1)$ curve (Figure 7) shows this dust feature as the knee of the profile rather than a massive layer feature indicated by the turbidity profile. This conceptual relationship suggests that over-emphasis is possible when dealing only with turbidity profiles.

The turbidity profile shows an upper stratospheric maximum with its lower terminus at 25 km. This altitude then, was the basis for choosing the upper stratospheric dust limit in Eq. (7). The maximum at 26 km occurs with sufficient frequency to be easily identified in the turbidity profile. The existence of such an aerosol concentration above 20 km is supported by the analysis of satellite photography reported by Maier, Dave, Dunkelman, and Evans (1967).

To establish upper altitude aerosol coefficients, a least square fit was computed for $\bar{\beta}_p(h, \lambda_1)$ from 26 to 32 km (Figure 9). The result, $H_p = 3.75$ km (in effect derived from 79 measurement points), was used in Eq. (8) to extend the values to 50 km. Miller (1967) obtained $H_p = 3.25$ km from a thorough analysis of rocket measurements acquired in 1964 for this altitude region. The overall profile from sea level to 50 km is presented in Figure 10 (Table 4.11). Since the




Figure 9. Expanded Scale for 26 to 32 km Altitude Region Showing $H_p = 3.75$ km for 79 Profile Mean; Aerosol Attenuation Coefficients, $\bar{\beta}_p(h, \lambda_1)$ vs Altitude; Least Square Fit Used to Extrapolate to 50 km; $\lambda_1 = 0.55\mu$




Figure 10. Comparison of Profiles. Aerosol attenuation coefficients $\beta_p(h, \lambda_1)$, with molecular $\beta_r(h, \lambda_1)$. The 1964 profile shows interpolation between 5 to 10 km; $\lambda_1 = 0.55\mu$

turbidity is proportional to the mixing ratio, the diminishing values for the extrapolation imply the aerosol source exists below 30 km. Should the source be of meteoric origin, the mixing ratio would tend to be constant or increase for altitudes 30 to 50 km.

Thus far we have selected a set of measurements for $\lambda_1 = 0.55\mu$ and provided reasons for its use. It would be in order now to examine some expressions leading to corresponding aerosol profiles for other wavelengths. If we consider a real atmosphere, the aerosol sizes within unit volume can be described by a size distribution function, $\psi(r)$. Various size distribution functions are in use: the Junge type power law (1963) with a choice of exponents discussed in detail by Bullrich (1964), a similar distribution modified by gaps observed by Fenn (1964), a log-Gaussian distribution used by Foitzik (1965), a composite distribution with components from several types. The optical-particle size relationship utilizes $\psi(r)$ such that

$$\beta_p(m, r, \lambda) = \int_{N_{r2}}^{N_{r1}} \sigma_p(m, r, \lambda) dN_p(r) \quad , \quad (9)$$

$$dN_p = N_0 \psi(r) dr \quad , \quad (10)$$

$$N_0(h) = C N_p(h) \quad . \quad (11)$$

β_p is the aerosol attenuation coefficient, m is the index of refraction, N_{r1} and N_{r2} are the aerosol number density limits established by the radii limits r_1 and r_2 , σ_p is the aerosol cross section for each particle, N_p is the total number of particles between r_1 and r_2 . For a given altitude, N_0 actually is proportional to the particle number density between r_1 and r_2 . Since the same size distribution function applies to all altitudes (an assumption), Eqs. (9), (10), and (11) are combined

$$\beta_p(h, \lambda) = C N_p(h) \int_{r_1}^{r_2} \sigma_p(r, \lambda) \psi(r) dr \quad . \quad (12)$$

Here, $C N_p(h)$ is placed outside the integral which now contains only factors that are independent of altitude; also, m is removed because subsequent considerations will pertain to particles without any distinction in refractive index. If Eq. (12) is normalized to sea level conditions, the integral cancels out. Then generally for the various wavelengths λ , and specifically for $\lambda_1 = 0.55\mu$, we have

$$\frac{\beta_p(h, \lambda)}{\beta_p(0, \lambda)} = \frac{\beta_p(h, \lambda_1)}{\beta_p(0, \lambda_1)} = \frac{N_p(h)}{N_p(0)} \quad (13)$$

or

$$\beta_p(h, \lambda) = \frac{\beta_p(0, \lambda)}{\beta_p(0, \lambda_1)} \cdot \beta_p(h, \lambda_1) \quad (14)$$

Equation (13) has been derived in this manner to demonstrate its compatibility with particle size considerations. Sea level conditions have been researched extensively by Curcio and Durbin (1959), Curcio, Knestrick, and Cosden (1961), Knestrick, Cosden, and Curcio (1961), Dunkelman (1952), Baum and Dunkelman (1955). The $\beta_p(0, \lambda)$ values for a 25 km M.R., based on the results of these authors, are shown in Figure 11 (see also Elterman, 1964). Utilizing these results, in conjunction with the $\hat{\beta}_p(h, \lambda_1)$ profile (Table 4.11), all requirements for the right-hand side of Eq. (14) are satisfied and an array of aerosol attenuation coefficients can be computed for all altitudes and wavelengths of interest.

The aerosol optical thickness from sea level to altitude h , $\tau_p(h, \lambda)$, and the aerosol optical thickness from some altitude h to space, $\tau_p^1(h, \lambda)$, are included in the model tabulations. The expressions for deriving these parameters have the same form as Eqs. (4) and (5).




Figure 11. Aerosol Attenuation Coefficients $\beta_p(0, \lambda)$ vs Wavelength at Sea Level for a Meteorological Range Approximating 25 km.
 A - derived from Baum and Dunkelman (1955)
 B - contained in Curcio, Knestrick, and Cosden (1961)

5. ATMOSPHERIC EXTINCTION

In this section, three sets of extinction parameters are considered: extinction coefficient, extinction optical thickness from sea level to a desired altitude, and extinction optical thickness from a desired altitude to space.

The atmospheric extinction coefficient β_{ext} is the sum of all the attenuating components:

$$\beta_{\text{ext}}(h, \lambda) = \beta_r(h, \lambda) + \beta_g(h, \lambda) + \beta_p(h, \lambda) \quad (15)$$

The extinction optical thickness from sea level to altitude h , $\tau_{\text{ext}}(h, \lambda)$, and the extinction optical thickness from some altitude h to space, $\tau'_{\text{ext}}(h, \lambda)$, are included in the tabulations of the attenuation model. The expression for deriving these parameters has the same form as Eqs. (4) and (5).

6. EXPLORATORY TRANSMISSION CALCULATIONS

Using the derived tabulations that follow, some exploratory calculations with extinction parameters (for any of the wavelengths) are demonstrated. Rayleigh, aerosol, and ozone parameters can be used similarly.

For horizontal transmission (T_h) over a path (d) at any altitude (h), the extinction coefficient

$$T_h = \exp \left[-\beta_{\text{ext}}(h, \lambda) \cdot d \right] \quad (16)$$

For vertical and slant-path transmission from sea level to a given altitude, at zenith angle θ for all wavelengths of interest

$$T_{0-h} = \exp \left[-\tau_{\text{ext}}(h) \cdot \sec \theta \right] \quad (17)$$

For vertical and slant-path transmission between two altitudes above sea level

$$T_{\Delta h} = \exp - \left[\tau_{\text{ext}}(h_2) - \tau_{\text{ext}}(h_1) \right] \cdot \sec \theta \quad (18)$$

For vertical and slant-path transmission from a given altitude out into space

$$T_{h-\infty} = \exp \left[-\tau'_{\text{ext}}(h) \sec \theta \right] \quad (19)$$

7. CONCLUDING REMARKS

The procedure for developing the aerosol attenuation profile is summarized as follows:

- (1) Various studies were compared and of these a set of measurements selected.
- (2) The choice of measurements (comprising 119 profiles from 2.76 to 34.4 km) was examined statistically. This resulted in the elimination of 40 profiles (December 1963 to March 1964 inclusive) characterized by a high volcanic dust component.
- (3) The mean of the 79 remaining profiles was extended to sea level and to 50 km respectively by reasonably supported extrapolations.
- (4) The overall profile then was developed laterally to obtain 21 additional profiles for the wavelengths of interest.

A significant aspect of the procedure is that the wavelength-height array of parameters was derived independently of the assumptions associated with conversion of a size distribution to an optical parameter.

For most purposes, calculations using the new parameters will be affected only moderately. For example at $\lambda_1 = 0.55\mu$, the 1964 Attenuation Model provides an extinction optical thickness, $\tau_{\text{ext}} = 0.331$, for a vertical air mass. The new parameters yield $\tau_{\text{ext}} = 0.379$, resulting in a transmission change of about 3-1/2 percent. However, for long path horizontal transmission calculations above 5 km and for long slant-path calculations entailing large zenith angles, the new aerosol parameters can function more significantly.

As mentioned previously, the Rayleigh and ozone parameters are unchanged.

8. TABULATION OF PARAMETERS

Tables 4.1 to 4.22, which follow, comprise the atmospheric attenuation model. Exponents are in computer notation; for example, read $2.86-3 = 2.86 \times 10^{-3}$ and $2.86\ 3$ as 2.86×10^3 .

Table 4.1 Parameters at 0.27 microns

Alt. (km)	h	Rayleigh atten. (km ⁻¹)	Rayleigh optical thick. (0-h)	Rayleigh optical thick. (h-∞)	Aerosol atten. (km ⁻¹)	Aerosol optical thick. (0-h)	Aerosol optical thick. (h-∞)	Ozone absorp. coeff. (km ⁻¹)	Ozone optical thick. (0-h)	Ozone optical thick. (h-∞)	Ext. coeff. (km ⁻¹)	Ext. optical thick. (0-h)	Ext. optical thick. (h-∞)
0	0	2.242	-1	1.928	2.90	-1	0.00	7.48	-1	0.00	1.27	0	73.346
1	1	2.071	-1	1.710	1.29	-1	-0.209	6.85	-1	0.716	1.02	0	1.143
2	2	1.975	-1	1.513	5.51	-2	-0.300	6.15	-1	1.356	8.58	-1	2.081
3	3	1.894	-1	1.335	2.31	-2	-0.336	5.25	-1	1.935	7.18	-1	2.869
4	4	1.825	-1	1.174	1.22	-2	-0.358	4.75	-1	2.435	6.39	-1	3.547
5	5	1.772	-1	1.030	9.21	-3	-0.358	4.54	-1	2.905	6.11	-1	4.172
6	6	1.730	-1	0.900	6.50	-3	-0.375	4.54	-1	3.354	5.83	-1	4.769
7	7	1.698	-1	0.793	6.04	-3	-0.382	4.69	-1	3.825	5.84	-1	5.353
8	8	1.675	-1	0.703	5.97	-3	-0.394	4.79	-1	4.239	5.83	-1	5.936
9	9	1.658	-1	0.630	5.97	-3	-0.405	5.90	-1	4.633	5.83	-1	6.569
10	10	1.645	-1	0.573	5.97	-3	-0.417	5.96	-1	5.046	5.83	-1	7.200
11	11	1.635	-1	0.527	5.97	-3	-0.430	5.96	-1	5.461	5.83	-1	7.832
12	12	1.628	-1	0.490	5.97	-3	-0.443	5.96	-1	5.876	5.83	-1	8.464
13	13	1.622	-1	0.461	5.97	-3	-0.456	5.96	-1	6.291	5.83	-1	9.096
14	14	1.617	-1	0.437	5.97	-3	-0.469	5.96	-1	6.706	5.83	-1	9.728
15	15	1.612	-1	0.417	5.97	-3	-0.482	5.96	-1	7.121	5.83	-1	10.360
16	16	1.607	-1	0.400	5.97	-3	-0.495	5.96	-1	7.536	5.83	-1	10.992
17	17	1.602	-1	0.385	5.97	-3	-0.508	5.96	-1	7.951	5.83	-1	11.624
18	18	1.597	-1	0.372	5.97	-3	-0.521	5.96	-1	8.366	5.83	-1	12.256
19	19	1.592	-1	0.360	5.97	-3	-0.534	5.96	-1	8.781	5.83	-1	12.888
20	20	1.587	-1	0.349	5.97	-3	-0.547	5.96	-1	9.196	5.83	-1	13.520
21	21	1.582	-1	0.339	5.97	-3	-0.560	5.96	-1	9.611	5.83	-1	14.152
22	22	1.577	-1	0.330	5.97	-3	-0.573	5.96	-1	10.026	5.83	-1	14.784
23	23	1.572	-1	0.322	5.97	-3	-0.586	5.96	-1	10.441	5.83	-1	15.416
24	24	1.567	-1	0.315	5.97	-3	-0.599	5.96	-1	10.856	5.83	-1	16.048
25	25	1.562	-1	0.309	5.97	-3	-0.612	5.96	-1	11.271	5.83	-1	16.680
26	26	1.557	-1	0.304	5.97	-3	-0.625	5.96	-1	11.686	5.83	-1	17.312
27	27	1.552	-1	0.300	5.97	-3	-0.638	5.96	-1	12.101	5.83	-1	17.944
28	28	1.547	-1	0.296	5.97	-3	-0.651	5.96	-1	12.516	5.83	-1	18.576
29	29	1.542	-1	0.293	5.97	-3	-0.664	5.96	-1	12.931	5.83	-1	19.208
30	30	1.537	-1	0.290	5.97	-3	-0.677	5.96	-1	13.346	5.83	-1	19.840
31	31	1.532	-1	0.288	5.97	-3	-0.690	5.96	-1	13.761	5.83	-1	20.472
32	32	1.527	-1	0.286	5.97	-3	-0.703	5.96	-1	14.176	5.83	-1	21.104
33	33	1.522	-1	0.284	5.97	-3	-0.716	5.96	-1	14.591	5.83	-1	21.736
34	34	1.517	-1	0.283	5.97	-3	-0.729	5.96	-1	15.006	5.83	-1	22.368
35	35	1.512	-1	0.282	5.97	-3	-0.742	5.96	-1	15.421	5.83	-1	22.999
36	36	1.507	-1	0.281	5.97	-3	-0.755	5.96	-1	15.836	5.83	-1	23.631
37	37	1.502	-1	0.280	5.97	-3	-0.768	5.96	-1	16.251	5.83	-1	24.263
38	38	1.497	-1	0.280	5.97	-3	-0.781	5.96	-1	16.666	5.83	-1	24.895
39	39	1.492	-1	0.280	5.97	-3	-0.794	5.96	-1	17.081	5.83	-1	25.527
40	40	1.487	-1	0.280	5.97	-3	-0.807	5.96	-1	17.496	5.83	-1	26.159
41	41	1.482	-1	0.280	5.97	-3	-0.820	5.96	-1	17.911	5.83	-1	26.791
42	42	1.477	-1	0.280	5.97	-3	-0.833	5.96	-1	18.326	5.83	-1	27.423
43	43	1.472	-1	0.280	5.97	-3	-0.846	5.96	-1	18.741	5.83	-1	28.055
44	44	1.467	-1	0.280	5.97	-3	-0.859	5.96	-1	19.156	5.83	-1	28.687
45	45	1.462	-1	0.280	5.97	-3	-0.872	5.96	-1	19.571	5.83	-1	29.319
46	46	1.457	-1	0.280	5.97	-3	-0.885	5.96	-1	19.986	5.83	-1	29.951
47	47	1.452	-1	0.280	5.97	-3	-0.898	5.96	-1	20.401	5.83	-1	30.583
48	48	1.447	-1	0.280	5.97	-3	-0.911	5.96	-1	20.816	5.83	-1	31.215
49	49	1.442	-1	0.280	5.97	-3	-0.924	5.96	-1	21.231	5.83	-1	31.847
50	50	1.437	-1	0.280	5.97	-3	-0.937	5.96	-1	21.646	5.83	-1	32.479

Table 4.2 Parameters at 0.28 microns

Alt. (km)	h	Rayleigh atten. (km ⁻¹)	Rayleigh optical thick. (0-h)	Rayleigh optical thick. (h-h ₀)	Aerosol atten. coeff. (km ⁻¹)	Aerosol optical thick. (0-h)	Aerosol optical thick. (h-h ₀)	Ozone absorp. coeff. (km ⁻¹)	Ozone optical thick. (0-h)	Ozone optical thick. (h-h ₀)	Ext. coeff. (km ⁻¹)	Ext. optical thick. (0-h)	Ext. optical thick. (h-h ₀)
0	0	1.948	-1	-0.000	2.70	-1	-0.000	3.77	-1	-0.000	8.42	-1	-0.000
1	1	1.767	-1	-0.184	1.19	-1	-0.232	3.45	-1	-0.361	6.41	-1	-0.742
2	2	1.600	-1	-0.354	5.13	-2	-0.179	3.11	-1	-0.630	5.22	-1	-1.323
3	3	1.445	-1	-0.505	1.133	-2	-0.111	2.65	-1	-0.977	4.31	-1	-1.800
4	4	1.303	-1	-0.643	1.14	-2	-0.095	2.40	-1	-1.230	3.81	-1	-2.206
5	5	1.171	-1	-0.767	8.58	-3	-0.085	2.34	-1	-1.457	3.60	-1	-2.576
6	6	1.050	-1	-0.877	6.05	-3	-0.077	2.29	-1	-1.698	3.40	-1	-2.926
7	7	9.390	-2	-0.977	5.52	-3	-0.071	2.36	-1	-1.931	3.36	-1	-3.264
8	8	8.359	-2	-1.065	5.79	-3	-0.066	2.42	-1	-2.170	3.31	-1	-3.598
9	9	7.426	-2	-1.144	5.55	-3	-0.060	2.98	-1	-2.440	3.31	-1	-3.952
10	10	6.574	-2	-1.214	5.42	-3	-0.055	3.71	-1	-2.774	4.42	-1	-4.362
11	11	5.800	-2	-1.274	5.08	-3	-0.049	4.88	-1	-3.203	5.51	-1	-4.858
12	12	4.959	-2	-1.329	5.33	-3	-0.044	6.58	-1	-3.776	7.13	-1	-5.490
13	13	4.238	-2	-1.375	4.32	-3	-0.039	8.95	-1	-4.553	9.43	-1	-6.318
14	14	3.623	-2	-1.414	4.02	-3	-0.034	1.01	0	-5.508	1.06	0	-7.317
15	15	3.095	-2	-1.449	4.33	-3	-0.029	1.05	0	-6.542	1.09	0	-8.390
16	16	2.647	-2	-1.476	4.31	-3	-0.025	1.09	0	-7.615	1.12	0	-9.496
17	17	2.262	-2	-1.501	4.25	-3	-0.021	1.18	0	-8.749	1.20	0	-10.659
18	18	1.934	-2	-1.522	4.12	-3	-0.017	1.29	0	-9.984	1.32	0	-11.919
19	19	1.653	-2	-1.540	3.67	-3	-0.013	1.51	0	-11.383	1.53	0	-13.340
20	20	1.414	-2	-1.555	2.55	-3	-0.010	1.74	0	-13.035	1.76	0	-14.980
21	21	1.204	-2	-1.564	1.35	-3	-0.008	1.95	0	-14.850	1.98	0	-16.839
22	22	1.026	-2	-1.579	1.39	-3	-0.006	2.10	0	-15.859	2.11	0	-18.872
23	23	0.745	-3	-1.589	1.05	-3	-0.005	2.05	0	-16.952	2.05	0	-20.976
24	24	0.623	-3	-1.597	0.82	-4	-0.004	2.05	0	-18.181	2.05	0	-23.057
25	25	0.546	-3	-1.603	0.69	-4	-0.003	1.91	0	-19.629	1.92	0	-25.042
26	26	0.466	-3	-1.609	0.61	-4	-0.002	1.73	0	-21.402	1.73	0	-26.866
27	27	0.458	-3	-1.614	0.53	-4	-0.002	1.49	0	-23.441	1.50	0	-28.683
28	28	0.398	-3	-1.619	0.42	-4	-0.001	1.30	0	-25.640	1.31	0	-29.887
29	29	0.345	-3	-1.622	0.32	-4	-0.001	1.13	0	-27.959	1.14	0	-31.110
30	30	0.292	-3	-1.626	0.24	-4	-0.001	0.97	-1	-30.105	0.96	-1	-32.159
31	31	0.251	-3	-1.629	0.17	-4	-0.001	0.84	-1	-31.003	0.84	-1	-33.061
32	32	0.215	-3	-1.631	0.15	-4	-0.001	0.73	-1	-31.785	0.73	-1	-33.845
33	33	0.184	-3	-1.633	0.13	-4	-0.000	0.67	-1	-32.455	0.67	-1	-34.517
34	34	0.157	-3	-1.634	0.11	-4	-0.000	0.61	-1	-33.021	0.61	-1	-35.084
35	35	0.134	-3	-1.636	0.09	-4	-0.000	0.57	-1	-33.506	0.57	-1	-35.572
36	36	0.115	-3	-1.637	0.08	-4	-0.000	0.53	-1	-33.926	0.53	-1	-35.992
37	37	0.091	-4	-1.638	0.07	-4	-0.000	0.49	-1	-34.277	0.49	-1	-36.345
38	38	0.073	-4	-1.639	0.06	-4	-0.000	0.46	-1	-34.571	0.46	-1	-36.640
39	39	0.056	-4	-1.640	0.05	-4	-0.000	0.43	-1	-34.820	0.43	-1	-36.890
40	40	0.043	-4	-1.640	0.05	-4	-0.000	0.40	-1	-35.034	0.40	-1	-37.102
41	41	0.035	-4	-1.641	0.04	-4	-0.000	0.37	-1	-35.213	0.37	-1	-37.284
42	42	0.028	-4	-1.642	0.04	-4	-0.000	0.35	-1	-35.357	0.35	-1	-37.428
43	43	0.022	-4	-1.642	0.03	-4	-0.000	0.33	-1	-35.469	0.33	-1	-37.541
44	44	0.018	-4	-1.642	0.03	-4	-0.000	0.31	-1	-35.558	0.31	-1	-37.630
45	45	0.015	-4	-1.643	0.02	-4	-0.000	0.29	-1	-35.628	0.29	-1	-37.700
46	46	0.012	-4	-1.643	0.02	-4	-0.000	0.27	-1	-35.682	0.27	-1	-37.755
47	47	0.009	-4	-1.643	0.02	-4	-0.000	0.25	-1	-35.724	0.25	-1	-37.797
48	48	0.007	-4	-1.644	0.02	-4	-0.000	0.23	-1	-35.758	0.23	-1	-37.831
49	49	0.005	-4	-1.644	0.01	-4	-0.000	0.21	-1	-35.784	0.21	-1	-37.858
50	50	0.003	-4	-1.644	0.01	-4	-0.000	0.19	-1	-35.806	0.19	-1	-37.880

Table 4.3 Parameters at 0.30 microns

Alt. (km)	Rayleigh atten. coeff. (km ⁻¹)	Rayleigh optical thick. (0-n)	Rayleigh optical thick. (h-∞)	Aerosol atten. coeff. (km ⁻¹)	Aerosol optical thick. (0-h)	Aerosol optical thick. (h-∞)	Ozone absorp. coeff. (km ⁻¹)	Ozone optical thick. (0-h)	Ozone optical thick. (h-∞)	Ext. coeff. (km ⁻¹)	Ext. optical thick. (0-h)	Ext. optical thick. (h-∞)
h	β_r	τ_r	τ'_r	β_p	τ_p	τ'_p	β_3	τ_3	τ'_3	β_{ext}	τ_{ext}	τ'_{ext}
0	1.446	-1	-0.00	2.60	-1	-0.00	3.60	-2	-0.00	4.41	-1	-0.00
1	1.312	-1	-0.138	1.14	-1	-0.244	3.23	-2	-0.34	2.79	-1	-0.360
2	1.188	-1	-0.263	0.94	-2	-0.269	2.96	-2	-0.66	1.98	-1	-0.598
3	1.073	-1	-0.376	0.86	-2	-0.304	2.52	-2	-0.93	1.53	-1	-0.773
4	0.972	-2	-0.477	1.10	-2	-0.320	2.28	-2	-1.17	1.31	-1	-0.915
5	0.893	-2	-0.569	0.86	-3	-0.330	2.23	-2	-1.40	1.18	-1	-1.039
6	0.792	-2	-0.651	0.58	-3	-0.337	2.18	-2	-1.62	1.06	-1	-1.151
7	0.695	-2	-0.725	0.41	-3	-0.342	2.15	-2	-1.84	0.97	-2	-1.252
8	0.607	-2	-0.791	0.31	-3	-0.348	2.10	-2	-2.07	0.89	-2	-1.346
9	0.513	-2	-0.849	0.22	-3	-0.353	2.04	-2	-2.32	0.89	-2	-1.436
10	0.481	-2	-0.901	0.20	-3	-0.358	1.98	-2	-2.64	0.89	-2	-1.525
11	0.406	-2	-0.947	0.24	-3	-0.364	1.91	-2	-3.05	0.89	-2	-1.617
12	0.382	-2	-0.987	0.25	-3	-0.369	1.84	-2	-3.60	1.05	-1	-1.717
13	0.317	-2	-1.021	0.21	-3	-0.373	1.76	-2	-4.34	1.22	-1	-1.830
14	0.260	-2	-1.050	0.17	-3	-0.378	1.68	-2	-5.25	1.28	-1	-1.955
15	0.259	-2	-1.075	0.17	-3	-0.383	1.60	-2	-6.23	1.48	-1	-2.083
16	0.196	-2	-1.096	0.15	-3	-0.387	1.52	-2	-7.26	1.79	-1	-2.210
17	0.168	-2	-1.114	0.10	-3	-0.391	1.42	-1	-8.34	1.97	-1	-2.341
18	0.143	-2	-1.130	0.09	-3	-0.395	1.32	-1	-9.51	2.08	-1	-2.478
19	0.123	-2	-1.143	0.08	-3	-0.399	1.23	-1	-1.08	1.97	-1	-2.628
20	0.105	-2	-1.154	0.07	-3	-0.402	1.16	-1	-1.23	1.79	-1	-2.797
21	0.093	-3	-1.164	0.07	-3	-0.406	1.09	-1	-1.41	1.97	-1	-2.985
22	0.085	-3	-1.172	0.06	-3	-0.409	1.02	-1	-1.60	2.08	-1	-3.187
23	0.077	-3	-1.179	0.06	-3	-0.412	0.95	-1	-1.80	2.07	-1	-3.395
24	0.071	-3	-1.185	0.06	-3	-0.415	0.88	-1	-2.00	2.01	-1	-3.599
25	0.065	-3	-1.191	0.06	-3	-0.418	0.82	-1	-2.20	1.87	-1	-3.793
26	0.060	-3	-1.195	0.06	-3	-0.421	0.76	-1	-2.40	1.69	-1	-3.972
27	0.055	-3	-1.199	0.06	-3	-0.424	0.71	-1	-2.60	1.46	-1	-4.129
28	0.050	-3	-1.202	0.06	-3	-0.427	0.66	-1	-2.80	1.28	-1	-4.266
29	0.045	-3	-1.205	0.06	-3	-0.430	0.61	-1	-3.00	1.11	-1	-4.386
30	0.040	-3	-1.207	0.06	-3	-0.433	0.56	-1	-3.20	0.96	-2	-4.488
31	0.035	-3	-1.209	0.06	-3	-0.436	0.51	-1	-3.40	0.82	-2	-4.576
32	0.030	-3	-1.211	0.06	-3	-0.439	0.46	-1	-3.60	0.69	-2	-4.652
33	0.025	-3	-1.212	0.06	-3	-0.442	0.41	-1	-3.80	0.57	-2	-4.717
34	0.020	-3	-1.213	0.06	-3	-0.445	0.36	-1	-4.00	0.46	-2	-4.773
35	0.015	-3	-1.214	0.06	-3	-0.448	0.31	-1	-4.20	0.36	-2	-4.820
36	0.010	-3	-1.215	0.06	-3	-0.451	0.26	-1	-4.40	0.26	-2	-4.861
37	0.005	-3	-1.216	0.06	-3	-0.454	0.21	-1	-4.60	0.17	-2	-4.895
38	0.000	-3	-1.217	0.06	-3	-0.457	0.16	-1	-4.80	0.09	-2	-4.924
39	0.000	-3	-1.217	0.06	-3	-0.460	0.11	-1	-5.00	0.05	-2	-4.948
40	0.000	-3	-1.218	0.06	-3	-0.463	0.06	-1	-5.20	0.03	-2	-4.969
41	0.000	-3	-1.218	0.06	-3	-0.466	0.01	-1	-5.40	0.01	-2	-4.987
42	0.000	-3	-1.219	0.06	-3	-0.469	0.00	-1	-5.60	0.00	-2	-5.001
43	0.000	-3	-1.219	0.06	-3	-0.472	0.00	-1	-5.80	0.00	-2	-5.012
44	0.000	-3	-1.219	0.06	-3	-0.475	0.00	-1	-6.00	0.00	-2	-5.021
45	0.000	-3	-1.220	0.06	-3	-0.478	0.00	-1	-6.20	0.00	-2	-5.028
46	0.000	-3	-1.220	0.06	-3	-0.481	0.00	-1	-6.40	0.00	-2	-5.033
47	0.000	-3	-1.220	0.06	-3	-0.484	0.00	-1	-6.60	0.00	-2	-5.037
48	0.000	-3	-1.220	0.06	-3	-0.487	0.00	-1	-6.80	0.00	-2	-5.041
49	0.000	-3	-1.220	0.06	-3	-0.490	0.00	-1	-7.00	0.00	-2	-5.043
50	0.000	-3	-1.221	0.06	-3	-0.493	0.00	-1	-7.20	0.00	-2	-5.045

Table 4.4 Parameters at 0.32 microns

Alt. (km)	h	Rayleigh atten. coeff. (km ⁻¹)	Rayleigh optical thick. (0-h)	Rayleigh optical thick. (h-∞)	Aerosol atten. coeff. (km ⁻¹)	Aerosol optical thick. (0-h)	Aerosol optical thick. (h-∞)	Ozone absorp. coeff. (km ⁻¹)	Ozone optical thick. (0-h)	Ozone optical thick. (h-∞)	Ext. coeff. (km ⁻¹)	Ext. optical thick. (0-h)	Ext. optical thick. (h-∞)
0	0	1.093	-1	-0.09	2.50	-1	-0.00	3.20	-3	-0.00	3.63	-1	1.628
1	1	9.962	-2	-1.05	1.10	-1	-0.180	2.93	-3	-0.03	2.13	-1	1.340
2	2	9.020	-2	-1.99	4.75	-2	-0.259	2.63	-3	-0.06	1.40	-1	1.163
3	3	8.168	-2	-2.85	1.39	-2	-0.292	2.44	-3	-0.08	1.04	-1	1.041
4	4	7.342	-2	-3.62	1.05	-2	-0.308	2.03	-3	-0.10	8.60	-2	0.881
5	5	6.599	-2	-4.32	7.94	-3	-0.317	1.98	-3	-0.12	7.59	-2	0.762
6	6	5.915	-2	-4.95	5.60	-3	-0.324	1.94	-3	-0.14	6.67	-2	0.666
7	7	5.287	-2	-5.50	5.21	-3	-0.329	2.00	-3	-0.16	6.01	-2	0.597
8	8	4.712	-2	-6.00	5.36	-3	-0.334	2.05	-3	-0.18	5.45	-2	0.554
9	9	4.195	-2	-6.45	5.14	-3	-0.340	2.52	-3	-0.21	4.95	-2	1.006
10	10	3.705	-2	-6.84	5.02	-3	-0.345	3.14	-3	-0.24	4.52	-2	1.053
11	11	3.269	-2	-7.13	4.70	-3	-0.350	4.13	-3	-0.27	4.15	-2	1.097
12	12	2.795	-2	-7.49	4.34	-3	-0.354	5.58	-3	-0.32	3.85	-2	1.137
13	13	2.383	-2	-7.75	4.36	-3	-0.359	7.59	-3	-0.39	3.60	-2	1.174
14	14	2.042	-2	-7.97	4.46	-3	-0.364	8.59	-3	-0.47	3.35	-2	1.209
15	15	1.745	-2	-8.16	4.19	-3	-0.368	8.93	-3	-0.55	3.06	-2	1.241
16	16	1.492	-2	-8.32	3.99	-3	-0.372	9.25	-3	-0.65	2.82	-2	1.270
17	17	1.275	-2	-8.46	3.94	-3	-0.376	9.97	-3	-0.74	2.67	-2	1.297
18	18	1.090	-2	-8.58	3.81	-3	-0.380	1.10	-2	-0.85	2.57	-2	1.324
19	19	9.319	-3	-8.68	3.21	-3	-0.383	1.28	-2	-0.96	2.53	-2	1.349
20	20	7.967	-3	-8.76	2.36	-3	-0.386	1.47	-2	-1.10	2.51	-2	1.374
21	21	6.785	-3	-8.84	1.71	-3	-0.388	1.65	-2	-1.26	2.50	-2	1.399
22	22	5.781	-3	-8.90	1.29	-3	-0.390	1.77	-2	-1.43	2.48	-2	1.424
23	23	4.929	-3	-8.95	9.84	-4	-0.391	1.78	-2	-1.61	2.37	-2	1.448
24	24	4.206	-3	-9.00	7.80	-4	-0.392	1.73	-2	-1.78	2.23	-2	1.471
25	25	3.592	-3	-9.04	5.57	-4	-0.393	1.62	-2	-1.95	2.04	-2	1.493
26	26	3.070	-3	-9.07	5.73	-4	-0.394	1.46	-2	-2.10	1.83	-2	1.514
27	27	2.625	-3	-9.10	4.38	-4	-0.394	1.27	-2	-2.24	1.57	-2	1.529
28	28	2.247	-3	-9.12	3.35	-4	-0.394	1.10	-2	-2.36	1.36	-2	1.544
29	29	1.925	-3	-9.14	2.58	-4	-0.394	9.61	-3	-2.46	1.18	-2	1.557
30	30	1.650	-3	-9.16	1.98	-4	-0.394	8.11	-3	-2.55	9.96	-3	1.567
31	31	1.415	-3	-9.18	1.51	-4	-0.395	7.12	-3	-2.63	8.69	-3	1.577
32	32	1.215	-3	-9.19	1.16	-4	-0.395	6.14	-3	-2.69	7.45	-3	1.585
33	33	1.037	-3	-9.20	8.86	-5	-0.395	5.23	-3	-2.75	6.35	-3	1.592
34	34	8.860	-4	-9.21	6.79	-5	-0.395	4.36	-3	-2.80	5.31	-3	1.598
35	35	7.594	-4	-9.22	5.21	-5	-0.395	3.87	-3	-2.84	4.68	-3	1.602
36	36	6.504	-4	-9.23	3.99	-5	-0.395	3.44	-3	-2.87	3.93	-3	1.607
37	37	5.587	-4	-9.23	3.05	-5	-0.395	2.71	-3	-2.90	3.30	-3	1.610
38	38	4.809	-4	-9.24	2.34	-5	-0.395	2.27	-3	-2.93	2.78	-3	1.613
39	39	4.146	-4	-9.24	1.79	-5	-0.395	1.95	-3	-2.95	2.38	-3	1.616
40	40	3.580	-4	-9.25	1.37	-5	-0.395	1.67	-3	-2.97	2.04	-3	1.618
41	41	3.097	-4	-9.25	1.05	-5	-0.395	1.36	-3	-2.98	1.69	-3	1.620
42	42	2.684	-4	-9.25	8.04	-6	-0.395	1.07	-3	-3.00	1.35	-3	1.622
43	43	2.329	-4	-9.25	6.16	-6	-0.395	8.35	-4	-3.00	1.07	-3	1.623
44	44	2.024	-4	-9.26	4.72	-6	-0.395	6.68	-4	-3.01	8.75	-4	1.624
45	45	1.762	-4	-9.26	3.61	-6	-0.395	5.17	-4	-3.02	6.97	-4	1.625
46	46	1.536	-4	-9.26	2.77	-6	-0.395	4.01	-4	-3.02	5.57	-4	1.625
47	47	1.341	-4	-9.26	2.12	-6	-0.395	3.17	-4	-3.03	4.53	-4	1.626
48	48	1.180	-4	-9.26	1.63	-6	-0.395	2.51	-4	-3.03	3.70	-4	1.626
49	49	1.042	-4	-9.26	1.24	-6	-0.395	2.00	-4	-3.03	3.06	-4	1.626
50	50	9.202	-5	-9.27	9.53	-7	-0.395	1.67	-4	-3.03	2.60	-4	1.627

Table 4.5 Parameters at 0.34 microns

Alt. (km) h	Rayleigh atten. coeff. (km ⁻¹) β_r	Rayleigh optical thick. (0-h) τ_r	Rayleigh optical thick. (h-∞) τ_r'	Aerosol atten. coeff. (km ⁻¹) β_p	Aerosol optical thick. (0-h) τ_p	Aerosol optical thick. (h-∞) τ_p'	Ozone absorp. coeff. (km ⁻¹) β_3	Ozone optical thick. (0-h) τ_3	Ozone optical thick. (h-∞) τ_3'	Ext. coeff. (km ⁻¹) β_{ext}	Ext. optical thick. (0-h) τ_{ext}	Ext. optical thick. (h-∞) τ_{ext}'
0	8.492-2	.000	.717	2.40-1	.000	.379	2.28-4	.000	.022	3.25-1	.000	1.120
1	7.707-2	.081	.636	1.66-1	.173	.297	2.09-4	.000	.021	1.83-1	.254	.866
2	6.978-2	.154	.563	1.54-2	.281	.281	1.88-4	.000	.021	1.16-1	.403	.717
3	6.303-2	.241	.497	1.91-2	.281	.281	1.60-4	.001	.021	8.23-2	.502	.618
4	5.680-2	.280	.437	1.01-2	.295	.084	1.45-4	.001	.021	6.71-2	.577	.543
5	5.105-2	.334	.383	7.63-3	.304	.075	1.41-4	.001	.021	5.88-2	.640	.480
6	4.576-2	.383	.335	5.38-3	.316	.069	1.33-4	.001	.021	5.13-2	.695	.425
7	4.090-2	.426	.292	5.00-3	.316	.063	1.43-4	.001	.020	4.60-2	.743	.376
8	3.645-2	.464	.253	5.15-3	.321	.058	1.46-4	.001	.020	4.17-2	.787	.332
9	3.238-2	.499	.219	4.34-3	.326	.053	1.80-4	.001	.020	3.75-2	.827	.293
10	2.867-2	.529	.188	4.82-3	.331	.049	2.24-4	.002	.020	3.37-2	.863	.257
11	2.529-2	.556	.161	4.51-3	.336	.044	2.94-4	.002	.020	3.01-2	.894	.225
12	2.162-2	.580	.138	4.74-3	.340	.039	3.97-4	.002	.019	2.68-2	.923	.197
13	1.848-2	.600	.118	4.37-3	.345	.035	5.41-4	.003	.019	2.34-2	.948	.172
14	1.580-2	.617	.101	4.28-3	.349	.030	6.12-4	.003	.018	2.07-2	.970	.150
15	1.350-2	.631	.086	4.03-3	.353	.026	6.36-4	.004	.018	1.82-2	.989	.130
16	1.154-2	.644	.074	3.83-3	.357	.022	7.10-4	.005	.016	1.60-2	1.007	.113
17	9.865-3	.654	.063	3.78-3	.361	.018	7.81-4	.005	.016	1.44-2	1.022	.098
18	8.433-3	.664	.054	3.66-3	.365	.015	9.09-4	.006	.016	1.29-2	1.035	.084
19	7.209-3	.671	.046	3.08-3	.368	.011	9.09-4	.007	.015	1.12-2	1.047	.072
20	6.164-3	.678	.039	2.26-3	.371	.009	1.05-3	.008	.014	9.48-3	1.058	.062
21	5.249-3	.684	.034	1.64-3	.373	.007	1.18-3	.009	.013	8.07-3	1.067	.053
22	4.472-3	.689	.029	1.23-3	.374	.005	1.26-3	.010	.011	6.97-3	1.074	.046
23	3.813-3	.693	.025	9.45-4	.375	.004	1.27-3	.011	.010	6.03-3	1.081	.039
24	3.254-3	.696	.021	7.49-4	.376	.003	1.24-3	.013	.009	5.24-3	1.086	.034
25	2.779-3	.699	.018	6.30-4	.377	.003	1.15-3	.014	.008	4.56-3	1.091	.029
26	2.375-3	.702	.016	5.50-4	.377	.002	1.04-3	.015	.007	3.97-3	1.095	.024
27	2.031-3	.704	.013	4.21-4	.378	.002	9.02-4	.016	.006	3.35-3	1.099	.021
28	1.738-3	.706	.012	3.22-4	.378	.001	7.87-4	.017	.005	2.85-3	1.102	.018
29	1.489-3	.707	.010	2.48-4	.378	.001	6.85-4	.018	.004	2.42-3	1.105	.015
30	1.276-3	.709	.009	1.90-4	.379	.001	5.78-4	.018	.003	2.04-3	1.107	.013
31	1.095-3	.710	.007	1.45-4	.379	.001	5.08-4	.019	.003	1.75-3	1.109	.011
32	9.397-4	.711	.006	1.11-4	.379	.000	4.36-4	.019	.002	1.49-3	1.110	.009
33	8.023-4	.712	.005	8.51-5	.379	.000	3.72-4	.020	.002	1.26-3	1.112	.008
34	6.854-4	.713	.005	6.52-5	.379	.000	3.10-4	.020	.002	1.06-3	1.113	.007
35	5.867-4	.713	.004	5.00-5	.379	.000	2.76-4	.020	.001	9.13-4	1.114	.006
36	5.031-4	.714	.004	3.83-5	.379	.000	2.31-4	.020	.001	7.72-4	1.115	.005
37	4.323-4	.714	.003	2.93-5	.379	.000	1.93-4	.021	.001	6.95-4	1.116	.004
38	3.720-4	.715	.003	2.25-5	.379	.000	1.62-4	.021	.001	5.56-4	1.116	.004
39	3.207-4	.715	.002	1.72-5	.379	.000	1.39-4	.021	.001	4.77-4	1.117	.003
40	2.770-4	.715	.002	1.42-5	.379	.000	1.19-4	.021	.000	4.09-4	1.117	.003
41	2.396-4	.716	.002	1.01-5	.379	.000	9.73-5	.021	.000	3.47-4	1.117	.002
42	2.076-4	.716	.002	7.72-6	.379	.000	7.62-5	.021	.000	2.91-4	1.118	.002
43	1.802-4	.716	.001	5.91-6	.379	.000	5.95-5	.021	.000	2.46-4	1.118	.002
44	1.566-4	.716	.001	4.53-6	.379	.000	4.76-5	.021	.000	2.09-4	1.118	.001
45	1.363-4	.716	.001	3.46-6	.379	.000	3.69-5	.022	.000	1.77-4	1.118	.001
46	1.188-4	.716	.001	2.66-6	.379	.000	2.85-5	.022	.000	1.50-4	1.119	.001
47	1.037-4	.717	.001	2.04-6	.379	.000	2.26-5	.022	.000	1.28-4	1.119	.001
48	9.128-5	.717	.001	1.56-6	.379	.000	1.79-5	.022	.000	1.11-4	1.119	.001
49	8.051-5	.717	.001	1.19-6	.379	.000	1.43-5	.022	.000	9.61-5	1.119	.001
50	7.119-5	.717	.001	9.14-7	.379	.000	1.19-5	.022	.000	8.40-5	1.119	.001

Table 4.6 Parameters at 0.36 microns

Alt. (km)	h	Rayleigh coeff. (km ⁻¹)	Rayleigh optical thick. (0-h)	Rayleigh optical thick. (h-∞)	Aerosol atten. coeff. (km ⁻¹)	Aerosol optical thick. (0-h)	Aerosol optical thick. (h-∞)	Ozone absorp. coeff. (km ⁻¹)	Ozone optical thick. (0-h)	Ozone optical thick. (h-∞)	Ext. coeff. (km ⁻¹)	Ext. optical thick. (0-h)	Ext. optical thick. (h-∞)
		β_r	τ_r	τ'_r	β_p	τ_p	τ'_p	β_3	τ_3	τ'_3	β_{ext}	τ_{ext}	τ'_{ext}
0	0	6.678 -2	-0.00	-0.64	2.40 -1	-0.00	-0.379	6.41 -6	-0.00	-0.01	3.07 -1	-0.00	-0.945
1	1	6.060 -2	-0.04	-0.501	1.06 -1	-0.173	-0.207	5.87 -6	-0.00	-0.01	1.66 -1	-0.236	-0.709
2	2	5.487 -2	-0.121	-0.443	4.56 -2	-0.248	-0.131	5.27 -6	-0.00	-0.01	1.00 -1	-0.370	-0.575
3	3	4.957 -2	-0.173	-0.391	1.91 -2	-0.281	-0.099	4.50 -6	-0.00	-0.01	6.87 -2	-0.454	-0.491
4	4	4.467 -2	-0.220	-0.344	1.01 -2	-0.295	-0.084	4.07 -6	-0.00	-0.01	5.48 -2	-0.516	-0.429
5	5	4.015 -2	-0.263	-0.301	7.63 -3	-0.304	-0.075	3.98 -6	-0.00	-0.01	4.78 -2	-0.567	-0.378
6	6	3.599 -2	-0.301	-0.263	5.38 -3	-0.311	-0.069	3.83 -6	-0.00	-0.01	4.14 -2	-0.612	-0.333
7	7	3.216 -2	-0.335	-0.229	5.00 -3	-0.316	-0.063	4.01 -6	-0.00	-0.01	3.72 -2	-0.651	-0.294
8	8	2.866 -2	-0.365	-0.199	5.15 -3	-0.321	-0.058	4.10 -6	-0.00	-0.01	3.36 -2	-0.687	-0.258
9	9	2.546 -2	-0.392	-0.172	4.94 -3	-0.326	-0.053	5.06 -6	-0.00	-0.01	3.04 -2	-0.719	-0.226
10	10	2.254 -2	-0.416	-0.148	4.82 -3	-0.331	-0.049	6.30 -6	-0.00	-0.01	2.74 -2	-0.748	-0.197
11	11	1.989 -2	-0.437	-0.127	4.51 -3	-0.336	-0.044	8.28 -6	-0.00	-0.01	2.44 -2	-0.774	-0.172
12	12	1.701 -2	-0.456	-0.108	4.74 -3	-0.340	-0.039	1.12 -5	-0.00	-0.01	2.18 -2	-0.797	-0.148
13	13	1.453 -2	-0.471	-0.093	4.37 -3	-0.345	-0.035	1.52 -5	-0.00	-0.01	1.89 -2	-0.817	-0.128
14	14	1.242 -2	-0.485	-0.079	4.28 -3	-0.349	-0.030	1.72 -5	-0.00	-0.01	1.67 -2	-0.835	-0.110
15	15	1.062 -2	-0.496	-0.068	4.03 -3	-0.353	-0.026	1.79 -5	-0.00	-0.00	1.47 -2	-0.851	-0.095
16	16	9.075 -3	-0.506	-0.058	3.83 -3	-0.357	-0.022	1.85 -5	-0.00	-0.00	1.29 -2	-0.864	-0.081
17	17	7.758 -3	-0.515	-0.050	3.78 -3	-0.361	-0.018	2.00 -5	-0.00	-0.00	1.16 -2	-0.877	-0.069
18	18	6.632 -3	-0.522	-0.042	3.65 -3	-0.365	-0.015	2.20 -5	-0.00	-0.00	1.03 -2	-0.888	-0.058
19	19	5.669 -3	-0.528	-0.036	3.08 -3	-0.368	-0.011	2.56 -5	-0.00	-0.00	8.78 -3	-0.897	-0.046
20	20	4.867 -3	-0.533	-0.031	2.26 -3	-0.371	-0.009	2.95 -5	-0.00	-0.00	7.14 -3	-0.905	-0.034
21	21	4.127 -3	-0.538	-0.026	1.64 -3	-0.373	-0.007	3.31 -5	-0.00	-0.00	5.80 -3	-0.911	-0.028
22	22	3.517 -3	-0.541	-0.023	1.23 -3	-0.374	-0.005	3.55 -5	-0.00	-0.00	4.79 -3	-0.917	-0.024
23	23	2.999 -3	-0.545	-0.019	9.45 -4	-0.375	-0.004	3.56 -5	-0.00	-0.00	3.98 -3	-0.921	-0.020
24	24	2.559 -3	-0.547	-0.017	7.49 -4	-0.376	-0.003	3.47 -5	-0.00	-0.00	3.34 -3	-0.925	-0.017
25	25	2.185 -3	-0.549	-0.014	6.30 -4	-0.377	-0.003	3.24 -5	-0.00	-0.00	2.85 -3	-0.928	-0.015
26	26	1.867 -3	-0.552	-0.012	5.50 -4	-0.377	-0.002	2.93 -5	-0.00	-0.00	2.45 -3	-0.931	-0.012
27	27	1.597 -3	-0.554	-0.011	4.21 -4	-0.378	-0.002	2.54 -5	-0.00	-0.00	2.04 -3	-0.935	-0.010
28	28	1.367 -3	-0.555	-0.009	3.22 -4	-0.378	-0.001	2.21 -5	-0.00	-0.00	1.71 -3	-0.935	-0.009
29	29	1.171 -3	-0.556	-0.008	2.48 -4	-0.378	-0.001	1.93 -5	-0.00	-0.00	1.44 -3	-0.936	-0.008
30	30	1.004 -3	-0.557	-0.007	1.90 -4	-0.379	-0.001	1.63 -5	-0.00	-0.00	1.21 -3	-0.938	-0.006
31	31	8.609 -4	-0.558	-0.006	1.45 -4	-0.379	-0.001	1.43 -5	-0.00	-0.00	1.02 -3	-0.939	-0.005
32	32	7.389 -4	-0.559	-0.005	1.11 -4	-0.379	-0.000	1.23 -5	-0.00	-0.00	8.62 -4	-0.940	-0.005
33	33	6.309 -4	-0.560	-0.004	8.51 -5	-0.379	-0.000	1.05 -5	-0.00	-0.00	7.26 -4	-0.940	-0.005
34	34	5.390 -4	-0.560	-0.004	6.52 -5	-0.379	-0.000	8.73 -6	-0.00	-0.00	6.13 -4	-0.941	-0.004
35	35	4.614 -4	-0.561	-0.003	5.00 -5	-0.379	-0.000	7.76 -6	-0.00	-0.00	5.19 -4	-0.942	-0.003
36	36	3.957 -4	-0.561	-0.003	3.83 -5	-0.379	-0.000	6.50 -6	-0.00	-0.00	4.40 -4	-0.942	-0.003
37	37	3.369 -4	-0.562	-0.002	2.93 -5	-0.379	-0.000	5.44 -6	-0.00	-0.00	3.75 -4	-0.943	-0.003
38	38	2.926 -4	-0.562	-0.002	2.25 -5	-0.379	-0.000	4.55 -6	-0.00	-0.00	3.20 -4	-0.943	-0.002
39	39	2.522 -4	-0.562	-0.002	1.72 -5	-0.379	-0.000	3.91 -6	-0.00	-0.00	2.73 -4	-0.943	-0.002
40	40	2.178 -4	-0.563	-0.002	1.32 -5	-0.379	-0.000	3.35 -6	-0.00	-0.00	2.34 -4	-0.943	-0.002
41	41	1.884 -4	-0.563	-0.001	1.01 -5	-0.379	-0.000	2.74 -6	-0.00	-0.00	2.01 -4	-0.944	-0.001
42	42	1.633 -4	-0.563	-0.001	7.72 -6	-0.379	-0.000	2.14 -6	-0.00	-0.00	1.73 -4	-0.944	-0.001
43	43	1.417 -4	-0.563	-0.001	5.91 -6	-0.379	-0.000	1.67 -6	-0.00	-0.00	1.49 -4	-0.944	-0.001
44	44	1.231 -4	-0.563	-0.001	4.53 -6	-0.379	-0.000	1.34 -6	-0.00	-0.00	1.29 -4	-0.944	-0.001
45	45	1.072 -4	-0.563	-0.001	3.56 -6	-0.379	-0.000	1.04 -6	-0.00	-0.00	1.12 -4	-0.944	-0.001
46	46	9.345 -5	-0.563	-0.001	2.56 -6	-0.379	-0.000	8.03 -7	-0.00	-0.00	9.69 -5	-0.944	-0.001
47	47	8.158 -5	-0.563	-0.001	2.04 -6	-0.379	-0.000	6.35 -7	-0.00	-0.00	8.43 -5	-0.944	-0.001
48	48	7.178 -5	-0.564	-0.001	1.56 -6	-0.379	-0.000	5.02 -7	-0.00	-0.00	7.38 -5	-0.945	-0.001
49	49	6.339 -5	-0.564	-0.001	1.19 -6	-0.379	-0.000	4.01 -7	-0.00	-0.00	6.50 -5	-0.945	-0.001
50	50	5.598 -5	-0.564	-0.000	9.14 -7	-0.379	-0.000	3.35 -7	-0.00	-0.00	5.72 -5	-0.945	-0.000

Table 4.7 Parameters at 0.38 microns

Alt. (km)	h	Rayleigh atten. coeff. (km ⁻¹)	Rayleigh optical thick. (0-h)	Rayleigh optical thick. (h-∞)	Aerosol atten. coeff. (km ⁻¹)	Aerosol optical thick. (0-h)	Aerosol optical thick. (h-∞)	Ozone absorp. coeff. (km ⁻¹)	Ozone optical thick. (0-h)	Ozone optical thick. (h-∞)	Ext. coeff. (km ⁻¹)	Ext. optical thick. (0-h)	Ext. optical thick. (h-∞)
0	0	5.327 -2	.000	.450	2.30 -1	.000	.364	0.	.000	.000	2.83 -1	.000	.814
1	1	4.834 -2	.051	.399	1.01 -1	.166	.198	0.	.000	.000	1.50 -1	.000	.598
2	2	4.377 -2	.097	.353	4.37 -2	.238	.126	0.	.000	.000	8.74 -2	.335	.480
3	3	3.954 -2	.136	.312	1.83 -2	.269	.095	0.	.000	.000	5.79 -2	.408	.407
4	4	3.563 -2	.176	.274	9.69 -3	.283	.081	0.	.000	.000	4.53 -2	.459	.355
5	5	3.202 -2	.210	.240	7.31 -3	.292	.072	0.	.000	.000	3.93 -2	.501	.313
6	6	2.871 -2	.240	.210	5.15 -3	.298	.066	0.	.000	.000	3.39 -2	.538	.276
7	7	2.566 -2	.267	.183	4.79 -3	.303	.061	0.	.000	.000	3.04 -2	.570	.244
8	8	2.286 -2	.291	.159	4.93 -3	.308	.056	0.	.000	.000	2.78 -2	.599	.215
9	9	2.031 -2	.313	.137	4.73 -3	.312	.051	0.	.000	.000	2.50 -2	.626	.189
10	10	1.798 -2	.332	.118	4.61 -3	.317	.046	0.	.000	.000	2.26 -2	.650	.165
11	11	1.586 -2	.349	.101	4.32 -3	.322	.042	0.	.000	.000	2.02 -2	.671	.144
12	12	1.356 -2	.364	.086	4.54 -3	.326	.038	0.	.000	.000	1.81 -2	.690	.124
13	13	1.159 -2	.376	.074	4.19 -3	.330	.033	0.	.000	.000	1.58 -2	.707	.107
14	14	9.908 -3	.387	.063	4.11 -3	.335	.029	0.	.000	.000	1.40 -2	.722	.092
15	15	8.469 -3	.396	.054	3.86 -3	.339	.025	0.	.000	.000	1.23 -2	.735	.079
16	16	7.239 -3	.404	.046	3.67 -3	.342	.021	0.	.000	.000	1.09 -2	.747	.068
17	17	6.188 -3	.410	.039	3.62 -3	.346	.018	0.	.000	.000	9.81 -3	.757	.057
18	18	5.290 -3	.416	.034	3.51 -3	.349	.014	0.	.000	.000	8.80 -3	.766	.048
19	19	4.522 -3	.421	.029	2.96 -3	.353	.011	0.	.000	.000	7.48 -3	.775	.040
20	20	3.866 -3	.425	.025	2.17 -3	.355	.008	0.	.000	.000	6.04 -3	.781	.033
21	21	3.292 -3	.429	.021	1.57 -3	.357	.006	0.	.000	.000	4.86 -3	.787	.028
22	22	2.805 -3	.432	.018	1.18 -3	.359	.005	0.	.000	.000	3.99 -3	.791	.023
23	23	2.392 -3	.434	.016	9.05 -4	.360	.004	0.	.000	.000	3.30 -3	.795	.020
24	24	2.041 -3	.437	.013	7.18 -4	.360	.003	0.	.000	.000	2.76 -3	.798	.017
25	25	1.743 -3	.439	.011	6.04 -4	.361	.003	0.	.000	.000	2.35 -3	.803	.014
26	26	1.490 -3	.440	.010	5.27 -4	.362	.002	0.	.000	.000	2.02 -3	.804	.012
27	27	1.274 -3	.442	.008	4.03 -4	.362	.002	0.	.000	.000	1.68 -3	.806	.010
28	28	1.090 -3	.443	.007	3.09 -4	.362	.001	0.	.000	.000	1.40 -3	.806	.008
29	29	9.340 -4	.444	.006	2.37 -4	.363	.001	0.	.000	.000	1.17 -3	.807	.007
30	30	8.006 -4	.445	.005	1.82 -4	.363	.001	0.	.000	.000	9.83 -4	.808	.006
31	31	6.867 -4	.445	.005	1.39 -4	.363	.001	0.	.000	.000	8.26 -4	.809	.005
32	32	5.894 -4	.446	.004	1.06 -4	.363	.000	0.	.000	.000	6.96 -4	.810	.004
33	33	5.033 -4	.447	.003	8.15 -5	.363	.000	0.	.000	.000	5.85 -4	.811	.004
34	34	4.300 -4	.447	.003	6.24 -5	.363	.000	0.	.000	.000	4.92 -4	.811	.003
35	35	3.680 -4	.447	.003	4.79 -5	.363	.000	0.	.000	.000	4.16 -4	.812	.003
36	36	3.156 -4	.448	.002	3.67 -5	.363	.000	0.	.000	.000	3.52 -4	.812	.002
37	37	2.711 -4	.448	.002	2.81 -5	.363	.000	0.	.000	.000	2.99 -4	.812	.002
38	38	2.334 -4	.448	.002	2.15 -5	.364	.000	0.	.000	.000	2.55 -4	.813	.002
39	39	2.012 -4	.449	.001	1.64 -5	.364	.000	0.	.000	.000	2.18 -4	.813	.002
40	40	1.738 -4	.449	.001	1.26 -5	.364	.000	0.	.000	.000	1.86 -4	.813	.001
41	41	1.503 -4	.449	.001	9.67 -6	.364	.000	0.	.000	.000	1.60 -4	.813	.001
42	42	1.302 -4	.449	.001	7.39 -6	.364	.000	0.	.000	.000	1.38 -4	.813	.001
43	43	1.130 -4	.449	.001	5.66 -6	.364	.000	0.	.000	.000	1.19 -4	.814	.001
44	44	9.823 -5	.449	.001	4.34 -6	.364	.000	0.	.000	.000	1.03 -4	.814	.001
45	45	8.550 -5	.449	.001	3.32 -6	.364	.000	0.	.000	.000	8.88 -5	.814	.001
46	46	7.454 -5	.449	.001	2.55 -6	.364	.000	0.	.000	.000	7.71 -5	.814	.001
47	47	6.508 -5	.449	.001	1.95 -6	.364	.000	0.	.000	.000	6.70 -5	.814	.001
48	48	5.726 -5	.450	.000	1.50 -6	.364	.000	0.	.000	.000	5.88 -5	.814	.000
49	49	5.056 -5	.450	.000	1.14 -6	.364	.000	0.	.000	.000	5.17 -5	.814	.000
50	50	4.465 -5	.450	.000	8.76 -7	.364	.000	0.	.000	.000	4.55 -5	.814	.000

Table 4.8 Parameters at 0.40 microns

Alt. (km)	h	Rayleigh atten. coeff. (km ⁻¹)	Rayleigh optical thick. (0-h)	Rayleigh optical thick. (h-∞)	Aerosol atten. coeff. (km ⁻¹)	Aerosol optical thick. (0-h)	Aerosol optical thick. (h-∞)	Ozone absorp. coeff. (km ⁻¹)	Ozone optical thick. (0-h)	Ozone optical thick. (h-∞)	Ext. coeff. (km ⁻¹)	Ext. optical thick. (0-h)	Ext. optical thick. (h-∞)
0	0	4.303 -2	-0.00	-0.54	2.00 -1	-0.00	-0.16	0.	-0.00	-0.00	2.43 -1	-0.00	-0.00
1	1	3.905 -2	-0.41	-0.32	8.80 -2	-0.14	-0.17	0.	-0.00	-0.00	1.27 -1	-0.15	-0.15
2	2	3.536 -2	-0.73	-0.28	3.80 -2	-0.20	-0.10	0.	-0.00	-0.00	7.35 -2	-0.25	-0.25
3	3	3.194 -2	-1.12	-0.22	1.59 -2	-0.24	-0.07	0.	-0.00	-0.00	4.79 -2	-0.34	-0.34
4	4	2.878 -2	-1.42	-0.21	8.43 -3	-0.26	-0.04	0.	-0.00	-0.00	3.72 -2	-0.38	-0.38
5	5	2.587 -2	-1.69	-0.19	6.35 -3	-0.25	-0.03	0.	-0.00	-0.00	3.22 -2	-0.42	-0.42
6	6	2.319 -2	-1.94	-0.17	4.48 -3	-0.25	-0.02	0.	-0.00	-0.00	2.77 -2	-0.45	-0.45
7	7	2.073 -2	-2.16	-0.16	4.15 -3	-0.26	-0.02	0.	-0.00	-0.00	2.49 -2	-0.47	-0.47
8	8	1.847 -2	-2.45	-0.14	4.29 -3	-0.27	-0.04	0.	-0.00	-0.00	2.28 -2	-0.50	-0.50
9	9	1.641 -2	-2.53	-0.11	4.11 -3	-0.27	-0.04	0.	-0.00	-0.00	2.08 -2	-0.52	-0.52
10	10	1.453 -2	-2.68	-0.09	4.01 -3	-0.27	-0.04	0.	-0.00	-0.00	1.85 -2	-0.54	-0.54
11	11	1.281 -2	-2.82	-0.08	3.76 -3	-0.28	-0.03	0.	-0.00	-0.00	1.66 -2	-0.56	-0.56
12	12	1.096 -2	-2.94	-0.07	3.95 -3	-0.28	-0.03	0.	-0.00	-0.00	1.49 -2	-0.57	-0.57
13	13	9.365 -3	-3.04	-0.06	3.65 -3	-0.28	-0.02	0.	-0.00	-0.00	1.30 -2	-0.59	-0.59
14	14	8.004 -3	-3.12	-0.05	3.57 -3	-0.29	-0.02	0.	-0.00	-0.00	1.16 -2	-0.60	-0.60
15	15	6.841 -3	-3.20	-0.04	3.35 -3	-0.29	-0.02	0.	-0.00	-0.00	1.02 -2	-0.61	-0.61
16	16	5.848 -3	-3.26	-0.03	3.19 -3	-0.29	-0.01	0.	-0.00	-0.00	9.04 -3	-0.62	-0.62
17	17	4.999 -3	-3.32	-0.03	3.15 -3	-0.30	-0.01	0.	-0.00	-0.00	8.15 -3	-0.63	-0.63
18	18	4.273 -3	-3.36	-0.02	3.05 -3	-0.30	-0.01	0.	-0.00	-0.00	7.32 -3	-0.64	-0.64
19	19	3.653 -3	-3.40	-0.02	2.97 -3	-0.30	-0.00	0.	-0.00	-0.00	6.22 -3	-0.67	-0.67
20	20	3.123 -3	-3.44	-0.02	1.89 -3	-0.30	-0.00	0.	-0.00	-0.00	5.01 -3	-0.65	-0.65
21	21	2.660 -3	-3.46	-0.01	1.37 -3	-0.31	-0.00	0.	-0.00	-0.00	4.03 -3	-0.68	-0.68
22	22	2.266 -3	-3.49	-0.01	1.03 -3	-0.31	-0.00	0.	-0.00	-0.00	3.30 -3	-0.66	-0.66
23	23	1.932 -3	-3.51	-0.01	7.87 -4	-0.31	-0.00	0.	-0.00	-0.00	2.72 -3	-0.64	-0.64
24	24	1.649 -3	-3.53	-0.01	6.24 -4	-0.31	-0.00	0.	-0.00	-0.00	2.27 -3	-0.67	-0.67
25	25	1.408 -3	-3.54	-0.00	5.25 -4	-0.31	-0.00	0.	-0.00	-0.00	1.93 -3	-0.69	-0.69
26	26	1.203 -3	-3.56	-0.00	4.58 -4	-0.31	-0.00	0.	-0.00	-0.00	1.66 -3	-0.71	-0.71
27	27	1.029 -3	-3.57	-0.00	3.51 -4	-0.31	-0.00	0.	-0.00	-0.00	1.38 -3	-0.72	-0.72
28	28	8.809 -4	-3.58	-0.00	2.68 -4	-0.31	-0.00	0.	-0.00	-0.00	1.15 -3	-0.73	-0.73
29	29	7.545 -4	-3.58	-0.00	2.06 -4	-0.31	-0.00	0.	-0.00	-0.00	9.61 -4	-0.75	-0.75
30	30	6.467 -4	-3.59	-0.00	1.58 -4	-0.31	-0.00	0.	-0.00	-0.00	8.05 -4	-0.75	-0.75
31	31	5.547 -4	-3.60	-0.00	1.21 -4	-0.31	-0.00	0.	-0.00	-0.00	6.76 -4	-0.76	-0.76
32	32	4.762 -4	-3.60	-0.00	9.25 -5	-0.31	-0.00	0.	-0.00	-0.00	5.69 -4	-0.77	-0.77
33	33	4.065 -4	-3.61	-0.00	7.09 -5	-0.31	-0.00	0.	-0.00	-0.00	4.77 -4	-0.77	-0.77
34	34	3.473 -4	-3.61	-0.00	5.43 -5	-0.31	-0.00	0.	-0.00	-0.00	4.02 -4	-0.78	-0.78
35	35	2.973 -4	-3.61	-0.00	4.16 -5	-0.31	-0.00	0.	-0.00	-0.00	3.39 -4	-0.78	-0.78
36	36	2.549 -4	-3.62	-0.00	3.19 -5	-0.31	-0.00	0.	-0.00	-0.00	2.87 -4	-0.79	-0.79
37	37	2.190 -4	-3.62	-0.00	2.44 -5	-0.31	-0.00	0.	-0.00	-0.00	2.43 -4	-0.79	-0.79
38	38	1.885 -4	-3.62	-0.00	1.87 -5	-0.31	-0.00	0.	-0.00	-0.00	2.07 -4	-0.79	-0.79
39	39	1.625 -4	-3.62	-0.00	1.43 -5	-0.31	-0.00	0.	-0.00	-0.00	1.77 -4	-0.79	-0.79
40	40	1.404 -4	-3.62	-0.00	1.10 -5	-0.31	-0.00	0.	-0.00	-0.00	1.51 -4	-0.79	-0.79
41	41	1.214 -4	-3.63	-0.00	8.41 -6	-0.31	-0.00	0.	-0.00	-0.00	1.30 -4	-0.79	-0.79
42	42	1.052 -4	-3.63	-0.00	6.43 -6	-0.31	-0.00	0.	-0.00	-0.00	1.12 -4	-0.80	-0.80
43	43	9.129 -5	-3.63	-0.00	4.92 -6	-0.31	-0.00	0.	-0.00	-0.00	9.62 -5	-0.80	-0.80
44	44	7.925 -5	-3.63	-0.00	3.77 -6	-0.31	-0.00	0.	-0.00	-0.00	8.31 -5	-0.80	-0.80
45	45	6.907 -5	-3.63	-0.00	2.89 -6	-0.31	-0.00	0.	-0.00	-0.00	7.20 -5	-0.80	-0.80
46	46	6.021 -5	-3.63	-0.00	2.22 -6	-0.31	-0.00	0.	-0.00	-0.00	6.24 -5	-0.80	-0.80
47	47	5.257 -5	-3.63	-0.00	1.70 -6	-0.31	-0.00	0.	-0.00	-0.00	5.43 -5	-0.80	-0.80
48	48	4.625 -5	-3.63	-0.00	1.30 -6	-0.31	-0.00	0.	-0.00	-0.00	4.76 -5	-0.80	-0.80
49	49	4.085 -5	-3.63	-0.00	9.95 -7	-0.31	-0.00	0.	-0.00	-0.00	4.18 -5	-0.80	-0.80
50	50	3.607 -5	-3.63	-0.00	7.62 -7	-0.31	-0.00	0.	-0.00	-0.00	3.68 -5	-0.80	-0.80

Table 4.9 Parameters at 0.45 microns

Alt. (km)	h	Rayleigh atten. coeff. (km ⁻¹)	Rayleigh optical thick. (0-h)	τ_r	Rayleigh optical thick. (h-∞)	Aerosol atten. coeff. (km ⁻¹)	Aerosol optical thick. (0-h)	τ_p	Aerosol optical thick. (h-∞)	Ozone absorp. coeff. (km ⁻¹)	β_3	Ozone optical thick. (0-h)	τ_3	Ozone optical thick. (h-∞)	Ext. coeff. (km ⁻¹)	Ext. optical thick. (0-h)	Ext. optical thick. (h-∞)
0	0	2.644	-2	-0.00	-0.223	1.80	-1	-0.00	-0.285	1.25	-5	-0.00	-0.00	-0.00	2.06	-1	-0.00
1	1	2.400	-2	-0.05	-0.196	3.92	-2	-0.130	-0.155	1.14	-5	-0.00	-0.00	-0.00	1.03	-1	-0.00
2	2	2.173	-2	-0.06	-0.175	3.62	-2	-0.180	-0.098	1.03	-5	-0.00	-0.00	-0.00	5.59	-2	-0.234
3	3	1.963	-2	-0.09	-0.155	1.44	-2	-0.211	-0.074	0.75	-6	-0.00	-0.00	-0.00	3.40	-2	-0.279
4	4	1.769	-2	-0.08	-0.136	7.59	-3	-0.222	-0.056	7.91	-6	-0.00	-0.00	-0.00	2.53	-2	-0.309
5	5	1.590	-2	-0.04	-0.119	5.72	-3	-0.228	-0.053	7.73	-6	-0.00	-0.00	-0.00	2.16	-2	-0.332
6	6	1.425	-2	-0.19	-0.104	4.03	-3	-0.233	-0.052	7.56	-6	-0.00	-0.00	-0.00	1.83	-2	-0.352
7	7	1.274	-2	-0.13	-0.091	3.75	-3	-0.237	-0.048	7.80	-6	-0.00	-0.00	-0.00	1.65	-2	-0.370
8	8	1.135	-2	-0.15	-0.079	3.86	-3	-0.241	-0.044	7.98	-6	-0.00	-0.00	-0.00	1.52	-2	-0.386
9	9	1.008	-2	-0.15	-0.068	3.70	-3	-0.245	-0.040	9.83	-6	-0.00	-0.00	-0.00	1.38	-2	-0.400
10	10	8.926	-3	-0.16	-0.059	3.61	-3	-0.248	-0.036	1.22	-5	-0.00	-0.00	-0.00	1.25	-2	-0.413
11	11	7.874	-3	-0.17	-0.050	3.38	-3	-0.252	-0.033	1.61	-5	-0.00	-0.00	-0.00	1.13	-2	-0.425
12	12	6.733	-3	-0.18	-0.043	3.55	-3	-0.255	-0.029	2.17	-5	-0.00	-0.00	-0.00	1.03	-2	-0.436
13	13	5.755	-3	-0.18	-0.037	3.28	-3	-0.259	-0.026	2.96	-5	-0.00	-0.00	-0.00	9.07	-3	-0.446
14	14	4.915	-3	-0.19	-0.031	3.21	-3	-0.262	-0.023	3.35	-5	-0.00	-0.00	-0.00	8.16	-3	-0.454
15	15	4.204	-3	-0.19	-0.027	3.02	-3	-0.265	-0.020	3.48	-5	-0.00	-0.00	-0.00	7.26	-3	-0.462
16	16	3.593	-3	-0.20	-0.023	2.87	-3	-0.268	-0.017	3.60	-5	-0.00	-0.00	-0.00	6.50	-3	-0.469
17	17	3.072	-3	-0.20	-0.020	2.84	-3	-0.271	-0.014	3.88	-5	-0.00	-0.00	-0.00	5.95	-3	-0.475
18	18	2.626	-3	-0.20	-0.017	2.75	-3	-0.274	-0.011	4.27	-5	-0.00	-0.00	-0.00	5.41	-3	-0.481
19	19	2.265	-3	-0.20	-0.014	2.31	-3	-0.276	-0.009	4.97	-5	-0.00	-0.00	-0.00	4.61	-3	-0.486
20	20	1.919	-3	-0.21	-0.012	1.70	-3	-0.278	-0.007	5.74	-5	-0.00	-0.00	-0.00	3.87	-3	-0.490
21	21	1.634	-3	-0.21	-0.010	1.23	-3	-0.280	-0.005	6.44	-5	-0.00	-0.00	-0.00	2.93	-3	-0.493
22	22	1.393	-3	-0.21	-0.009	9.26	-4	-0.281	-0.004	6.89	-5	-0.00	-0.00	-0.00	2.39	-3	-0.496
23	23	1.187	-3	-0.21	-0.008	7.09	-4	-0.281	-0.003	6.93	-5	-0.00	-0.00	-0.00	1.97	-3	-0.498
24	24	1.013	-3	-0.21	-0.007	5.62	-4	-0.282	-0.003	6.75	-5	-0.00	-0.00	-0.00	1.64	-3	-0.500
25	25	8.652	-4	-0.21	-0.006	4.12	-4	-0.283	-0.002	6.30	-5	-0.00	-0.00	-0.00	1.40	-3	-0.501
26	26	7.394	-4	-0.21	-0.005	4.12	-4	-0.283	-0.002	5.70	-5	-0.00	-0.00	-0.00	1.21	-3	-0.503
27	27	6.324	-4	-0.21	-0.004	3.16	-4	-0.283	-0.001	4.93	-5	-0.00	-0.00	-0.00	9.97	-4	-0.504
28	28	5.413	-4	-0.22	-0.004	2.42	-4	-0.284	-0.001	4.30	-5	-0.00	-0.00	-0.00	8.26	-4	-0.505
29	29	4.634	-4	-0.22	-0.003	1.86	-4	-0.284	-0.001	3.74	-5	-0.00	-0.00	-0.00	6.87	-4	-0.505
30	30	3.874	-4	-0.22	-0.003	1.62	-4	-0.284	-0.001	3.16	-5	-0.00	-0.00	-0.00	5.71	-4	-0.506
31	31	3.409	-4	-0.22	-0.002	1.09	-4	-0.284	-0.000	2.78	-5	-0.00	-0.00	-0.00	4.77	-4	-0.507
32	32	2.926	-4	-0.22	-0.002	8.33	-5	-0.284	-0.000	2.39	-5	-0.00	-0.00	-0.00	4.00	-4	-0.507
33	33	2.499	-4	-0.22	-0.001	6.38	-5	-0.284	-0.000	2.04	-5	-0.00	-0.00	-0.00	3.34	-4	-0.507
34	34	2.134	-4	-0.22	-0.001	4.89	-5	-0.284	-0.000	1.70	-5	-0.00	-0.00	-0.00	3.29	-4	-0.508
35	35	1.827	-4	-0.22	-0.001	3.75	-5	-0.284	-0.000	1.51	-5	-0.00	-0.00	-0.00	2.35	-4	-0.508
36	36	1.567	-4	-0.22	-0.001	2.87	-5	-0.284	-0.000	1.26	-5	-0.00	-0.00	-0.00	1.98	-4	-0.508
37	37	1.365	-4	-0.22	-0.001	2.20	-5	-0.284	-0.000	1.06	-5	-0.00	-0.00	-0.00	1.67	-4	-0.508
38	38	1.158	-4	-0.22	-0.001	1.69	-5	-0.284	-0.000	0.85	-6	-0.00	-0.00	-0.00	1.42	-4	-0.509
39	39	9.987	-5	-0.22	-0.001	1.29	-5	-0.284	-0.000	7.59	-6	-0.00	-0.00	-0.00	1.20	-4	-0.509
40	40	8.625	-5	-0.22	-0.001	9.87	-6	-0.285	-0.000	6.51	-6	-0.00	-0.00	-0.00	1.03	-4	-0.509
41	41	7.461	-5	-0.22	-0.001	7.56	-6	-0.285	-0.000	5.32	-6	-0.00	-0.00	-0.00	0.75	-5	-0.509
42	42	6.464	-5	-0.22	-0.000	5.79	-6	-0.285	-0.000	4.16	-6	-0.00	-0.00	-0.00	0.76	-5	-0.509
43	43	5.610	-5	-0.22	-0.000	4.43	-6	-0.285	-0.000	3.25	-6	-0.00	-0.00	-0.00	6.38	-5	-0.509
44	44	4.876	-5	-0.22	-0.000	3.39	-6	-0.285	-0.000	2.60	-6	-0.00	-0.00	-0.00	5.48	-5	-0.509
45	45	4.244	-5	-0.22	-0.000	2.60	-6	-0.285	-0.000	2.02	-6	-0.00	-0.00	-0.00	4.71	-5	-0.509
46	46	3.700	-5	-0.22	-0.000	1.99	-6	-0.285	-0.000	1.56	-6	-0.00	-0.00	-0.00	4.06	-5	-0.509
47	47	3.230	-5	-0.22	-0.000	1.53	-6	-0.285	-0.000	1.24	-6	-0.00	-0.00	-0.00	3.51	-5	-0.509
48	48	2.842	-5	-0.22	-0.000	1.17	-6	-0.285	-0.000	0.76	-7	-0.00	-0.00	-0.00	3.06	-5	-0.509
49	49	2.510	-5	-0.22	-0.000	0.95	-7	-0.285	-0.000	7.80	-7	-0.00	-0.00	-0.00	2.68	-5	-0.509
50	50	2.217	-5	-0.22	-0.000	0.86	-7	-0.285	-0.000	6.51	-7	-0.00	-0.00	-0.00	2.35	-5	-0.509

Table 4.10 Parameters at 0.50 microns

Alt. (km)	h	Rayleigh atten. coeff. (km ⁻¹)	Rayleigh optical thick. (0-h)	Rayleigh optical thick. (h-∞)	Aerosol atten. coeff. (km ⁻¹)	Aerosol optical thick. (0-h)	Aerosol optical thick. (h-∞)	Ozone sharpp. coeff. (km ⁻¹)	Ozone optical thick. (0-h)	Ozone optical thick. (h-∞)	Ext. coeff. (km ⁻¹)	Ext. optical thick. (0-h)	Ext. optical thick. (h-∞)
0	0	1.716	-2	-0.00	1.67	-1	-0.00	1.23	-0.00	-0.12	1.84	-1	-0.00
1	1	1.557	-2	-0.16	3.17	-2	-0.12	1.12	-0.00	-0.12	8.91	-2	-0.00
2	2	1.410	-2	-0.31	3.17	-2	-0.173	1.01	-0.00	-0.11	4.59	-2	-0.204
3	3	1.273	-2	-0.45	1.33	-2	-0.195	8.63	-0.00	-0.11	2.61	-2	-0.240
4	4	1.148	-2	-0.57	7.04	-3	-0.206	7.80	-0.00	-0.11	1.86	-2	-0.263
5	5	1.031	-2	-0.68	5.31	-3	-0.212	7.62	-0.00	-0.11	1.57	-2	-0.280
6	6	9.245	-3	-0.77	3.74	-3	-0.216	7.45	-0.01	-0.11	1.31	-2	-0.294
7	7	8.263	-3	-0.86	3.48	-3	-0.220	7.49	-0.01	-0.11	1.18	-2	-0.307
8	8	7.364	-3	-0.94	3.58	-3	-0.223	7.87	-0.01	-0.11	1.10	-2	-0.318
9	9	6.541	-3	-1.01	3.44	-3	-0.227	9.59	-0.01	-0.11	1.01	-2	-0.329
10	10	5.791	-3	-1.07	3.35	-3	-0.230	1.21	-0.01	-0.11	9.26	-3	-0.338
11	11	5.129	-3	-1.12	3.14	-3	-0.233	1.59	-0.01	-0.11	8.41	-3	-0.347
12	12	4.369	-3	-1.17	3.30	-3	-0.237	2.14	-0.01	-0.10	7.88	-3	-0.355
13	13	3.734	-3	-1.21	3.04	-3	-0.240	2.92	-0.01	-0.10	7.07	-3	-0.363
14	14	3.191	-3	-1.25	2.98	-3	-0.243	3.43	-0.02	-0.10	6.50	-3	-0.369
15	15	2.728	-3	-1.28	2.80	-3	-0.246	3.43	-0.02	-0.10	5.87	-3	-0.376
16	16	2.331	-3	-1.30	2.66	-3	-0.249	3.55	-0.02	-0.09	5.35	-3	-0.381
17	17	1.993	-3	-1.32	2.63	-3	-0.251	3.83	-0.03	-0.09	5.01	-3	-0.386
18	18	1.704	-3	-1.34	2.55	-3	-0.254	4.21	-0.03	-0.08	4.67	-3	-0.391
19	19	1.456	-3	-1.36	2.15	-3	-0.256	4.90	-0.04	-0.08	4.09	-3	-0.396
20	20	1.245	-3	-1.37	1.57	-3	-0.258	5.66	-0.04	-0.07	3.39	-3	-0.399
21	21	1.060	-3	-1.38	1.14	-3	-0.259	6.35	-0.05	-0.07	2.84	-3	-0.403
22	22	9.035	-4	-1.39	8.59	-4	-0.260	6.80	-0.05	-0.06	2.44	-3	-0.405
23	23	7.783	-4	-1.40	6.57	-4	-0.261	6.83	-0.05	-0.05	2.11	-3	-0.407
24	24	6.574	-4	-1.41	5.21	-4	-0.262	6.66	-0.05	-0.05	1.84	-3	-0.409
25	25	5.614	-4	-1.41	4.39	-4	-0.262	6.21	-0.05	-0.04	1.62	-3	-0.411
26	26	4.798	-4	-1.42	3.83	-4	-0.263	5.62	-0.05	-0.04	1.42	-3	-0.413
27	27	4.103	-4	-1.42	2.93	-4	-0.263	4.86	-0.05	-0.03	1.19	-3	-0.414
28	28	3.512	-4	-1.43	2.24	-4	-0.263	4.24	-0.05	-0.03	1.00	-3	-0.415
29	29	3.008	-4	-1.43	1.72	-4	-0.263	3.59	-0.05	-0.02	8.42	-4	-0.416
30	30	2.578	-4	-1.43	1.32	-4	-0.264	3.12	-0.10	-0.02	7.01	-4	-0.417
31	31	2.212	-4	-1.43	1.01	-4	-0.264	2.74	-0.10	-0.02	5.96	-4	-0.417
32	32	1.898	-4	-1.44	7.73	-5	-0.264	2.35	-0.10	-0.01	5.02	-4	-0.418
33	33	1.621	-4	-1.44	5.92	-5	-0.264	2.01	-0.11	-0.01	4.22	-4	-0.418
34	34	1.385	-4	-1.44	4.53	-5	-0.264	1.87	-0.11	-0.01	3.51	-4	-0.419
35	35	1.185	-4	-1.44	3.48	-5	-0.264	1.49	-0.11	-0.01	3.02	-4	-0.419
36	36	1.015	-4	-1.44	2.66	-5	-0.264	1.25	-0.11	-0.01	2.53	-4	-0.419
37	37	8.732	-5	-1.44	2.04	-5	-0.264	1.04	-0.11	-0.01	2.12	-4	-0.420
38	38	7.516	-5	-1.44	1.56	-5	-0.264	8.73	-0.11	-0.00	1.78	-4	-0.420
39	39	6.480	-5	-1.44	1.19	-5	-0.264	7.49	-0.11	-0.00	1.52	-4	-0.420
40	40	5.596	-5	-1.45	9.15	-6	-0.264	6.42	-0.11	-0.00	1.29	-4	-0.420
41	41	4.841	-5	-1.45	7.02	-6	-0.264	5.24	-0.11	-0.00	1.08	-4	-0.420
42	42	4.194	-5	-1.45	5.37	-6	-0.264	4.11	-0.11	-0.00	8.84	-5	-0.420
43	43	3.640	-5	-1.45	4.11	-6	-0.264	3.21	-0.12	-0.00	7.26	-5	-0.420
44	44	3.153	-5	-1.45	3.15	-6	-0.264	2.57	-0.12	-0.00	6.05	-5	-0.420
45	45	2.754	-5	-1.45	2.41	-6	-0.264	1.99	-0.12	-0.00	4.98	-5	-0.421
46	46	2.401	-5	-1.45	1.85	-6	-0.264	1.54	-0.12	-0.00	4.12	-5	-0.421
47	47	2.096	-5	-1.45	1.42	-6	-0.264	1.22	-0.12	-0.00	3.46	-5	-0.421
48	48	1.844	-5	-1.45	1.09	-6	-0.264	9.63	-0.12	-0.00	2.92	-5	-0.421
49	49	1.628	-5	-1.45	8.31	-7	-0.264	7.69	-0.12	-0.00	2.48	-5	-0.421
50	50	1.438	-5	-1.45	6.36	-7	-0.264	6.42	-0.12	-0.00	2.14	-5	-0.421

Table 4.11 Parameters at 0.55 microns

Alt. (km) h	Rayleigh atten. coeff. (km ⁻¹) β_r	Rayleigh optical thick. (0-h) τ_r	Rayleigh optical thick. (h-∞) τ_r'	Aerosol atten. coeff. (km ⁻¹) β_p	Aerosol optical thick. (0-h) τ_p	Aerosol optical thick. (h-∞) τ_p'	Ozone absorp. coeff. (km ⁻¹) β_3	Ozone optical thick. (0-h) τ_3	Ozone optical thick. (h-∞) τ_3'	Ext. coeff. (km ⁻¹) β_{ext}	Ext. optical thick. (0-h) τ_{ext}	Ext. optical thick. (h-∞) τ_{ext}'
0	1.162-2	-0.00	-0.98	1.58-1	-0.00	-0.250	3.28-4	0.000	-0.31	1.70-1	0.000	0.379
1	1.055-2	-0.11	-0.87	6.95-2	-0.114	-0.136	3.00-4	0.000	-0.31	8.03-2	0.000	0.254
2	9.550-3	-0.21	-0.77	3.00-2	-0.163	-0.086	2.70-4	0.001	-0.30	3.98-2	0.000	0.194
3	6.627-3	-0.30	-0.68	1.26-2	-0.185	-0.065	2.30-4	0.001	-0.30	2.15-2	0.000	0.163
4	7.774-3	-0.38	-0.60	6.66-3	-0.194	-0.055	2.08-4	0.001	-0.30	1.46-2	0.000	0.145
5	6.987-3	-0.46	-0.52	5.02-3	-0.200	-0.049	2.03-4	0.001	-0.30	1.22-2	0.000	0.132
6	6.263-3	-0.52	-0.46	3.54-3	-0.205	-0.045	1.99-4	0.001	-0.30	1.00-2	0.000	0.121
7	5.598-3	-0.58	-0.40	3.29-3	-0.208	-0.042	2.05-4	0.002	-0.29	9.09-3	0.000	0.111
8	4.989-3	-0.64	-0.35	4.39-3	-0.211	-0.038	2.10-4	0.002	-0.29	8.59-3	0.000	0.102
9	4.431-3	-0.68	-0.30	3.25-3	-0.215	-0.035	2.59-4	0.002	-0.29	7.94-3	0.000	0.094
10	3.923-3	-0.72	-0.26	3.17-3	-0.218	-0.032	3.22-4	0.002	-0.29	7.42-3	0.000	0.086
11	3.461-3	-0.76	-0.22	2.97-3	-0.221	-0.029	4.23-4	0.003	-0.28	6.85-3	0.000	0.079
12	2.960-3	-0.79	-0.19	3.12-3	-0.224	-0.026	5.71-4	0.003	-0.28	6.45-3	0.000	0.073
13	2.529-3	-0.82	-0.16	2.88-3	-0.227	-0.023	7.77-4	0.004	-0.27	6.19-3	0.000	0.066
14	2.162-3	-0.84	-0.14	2.82-3	-0.230	-0.020	8.80-4	0.005	-0.26	5.86-3	0.000	0.060
15	1.848-3	-0.86	-0.12	2.65-3	-0.233	-0.017	9.14-4	0.006	-0.25	5.41-3	0.000	0.054
16	1.579-3	-0.88	-0.10	2.52-3	-0.235	-0.015	9.48-4	0.007	-0.24	5.05-3	0.000	0.049
17	1.350-3	-0.90	-0.09	2.49-3	-0.238	-0.012	1.02-3	0.008	-0.23	4.86-3	0.000	0.044
18	1.154-3	-0.91	-0.07	2.41-3	-0.240	-0.010	1.12-3	0.009	-0.22	4.69-3	0.000	0.040
19	9.867-4	-0.92	-0.06	2.03-3	-0.242	-0.007	1.31-3	0.010	-0.21	4.32-3	0.000	0.035
20	8.435-4	-0.93	-0.05	1.49-3	-0.244	-0.006	1.51-3	0.011	-0.20	3.84-3	0.000	0.031
21	7.183-4	-0.94	-0.05	1.08-3	-0.245	-0.004	1.69-3	0.013	-0.18	3.49-3	0.000	0.027
22	6.121-4	-0.94	-0.04	8.13-4	-0.246	-0.003	1.81-3	0.015	-0.16	3.24-3	0.000	0.024
23	5.219-4	-0.95	-0.03	6.22-4	-0.247	-0.003	1.82-3	0.016	-0.15	2.97-3	0.000	0.021
24	4.453-4	-0.95	-0.02	4.93-4	-0.248	-0.002	1.78-3	0.018	-0.13	2.71-3	0.000	0.018
25	3.803-4	-0.96	-0.02	4.15-4	-0.248	-0.002	1.66-3	0.020	-0.11	2.45-3	0.000	0.015
26	3.250-4	-0.96	-0.02	3.62-4	-0.248	-0.001	1.50-3	0.022	-0.10	2.19-3	0.000	0.013
27	2.780-4	-0.96	-0.02	2.77-4	-0.249	-0.001	1.30-3	0.023	-0.08	1.85-3	0.000	0.011
28	2.379-4	-0.97	-0.02	2.12-4	-0.249	-0.001	1.13-3	0.024	-0.07	1.58-3	0.000	0.009
29	2.048-4	-0.97	-0.01	1.63-4	-0.249	-0.001	9.84-4	0.025	-0.06	1.35-3	0.000	0.008
30	1.747-4	-0.97	-0.01	1.25-4	-0.249	-0.000	8.31-4	0.026	-0.05	1.13-3	0.000	0.007
31	1.498-4	-0.97	-0.01	9.55-5	-0.249	-0.000	7.30-4	0.027	-0.04	9.75-4	0.000	0.006
32	1.285-4	-0.97	-0.01	7.31-5	-0.249	-0.000	6.27-4	0.028	-0.03	8.29-4	0.000	0.005
33	1.098-4	-0.98	-0.01	5.60-5	-0.250	-0.000	5.35-4	0.028	-0.03	7.01-4	0.000	0.004
34	9.381-5	-0.98	-0.01	4.29-5	-0.250	-0.000	4.46-4	0.029	-0.02	5.83-4	0.000	0.003
35	8.030-5	-0.98	-0.01	3.29-5	-0.250	-0.000	3.97-4	0.029	-0.02	5.10-4	0.000	0.003
36	6.886-5	-0.98	-0.00	2.52-5	-0.250	-0.000	3.32-4	0.029	-0.02	4.26-4	0.000	0.002
37	5.916-5	-0.98	-0.00	1.93-5	-0.250	-0.000	2.78-4	0.030	-0.01	3.56-4	0.000	0.002
38	5.092-5	-0.98	-0.00	1.48-5	-0.250	-0.000	2.31-4	0.030	-0.01	2.98-4	0.000	0.002
39	4.390-5	-0.98	-0.00	1.13-5	-0.250	-0.000	2.00-4	0.030	-0.01	2.55-4	0.000	0.001
40	3.791-5	-0.98	-0.00	8.66-6	-0.250	-0.000	1.71-4	0.031	-0.01	2.18-4	0.000	0.001
41	3.279-5	-0.98	-0.00	6.64-6	-0.250	-0.000	1.40-4	0.031	-0.01	1.79-4	0.000	0.001
42	2.841-5	-0.98	-0.00	5.08-6	-0.250	-0.000	1.09-4	0.031	-0.00	1.43-4	0.000	0.001
43	2.466-5	-0.98	-0.00	3.89-6	-0.250	-0.000	8.56-5	0.031	-0.00	1.14-4	0.000	0.001
44	2.143-5	-0.98	-0.00	2.98-6	-0.250	-0.000	6.84-5	0.031	-0.00	9.29-5	0.000	0.001
45	1.866-5	-0.98	-0.00	2.28-6	-0.250	-0.000	5.30-5	0.031	-0.00	7.39-5	0.000	0.000
46	1.626-5	-0.98	-0.00	1.75-6	-0.250	-0.000	4.10-5	0.031	-0.00	5.90-5	0.000	0.000
47	1.420-5	-0.98	-0.00	1.34-6	-0.250	-0.000	3.25-5	0.031	-0.00	4.80-5	0.000	0.000
48	1.249-5	-0.98	-0.00	1.03-6	-0.250	-0.000	2.57-5	0.031	-0.00	3.92-5	0.000	0.000
49	1.103-5	-0.98	-0.00	7.86-7	-0.250	-0.000	2.05-5	0.031	-0.00	3.23-5	0.000	0.000
50	9.743-6	-0.98	-0.00	6.02-7	-0.250	-0.000	1.71-5	0.031	-0.00	2.75-5	0.000	0.000

Table 4.12 Parameters at 0.60 microns

Alt. (km)	h	Rayleigh atten. coeff. (km ⁻¹)	Rayleigh optical thick. (0-h)	Rayleigh optical thick. (h-∞)	Aerosol atten. coeff. (km ⁻¹)	Aerosol optical thick. (0-h)	Aerosol optical thick. (h-∞)	Ozone absorp. coeff. (km ⁻¹)	Ozone optical thick. (0-h)	Ozone optical thick. (h-∞)	Ext. coeff. (km ⁻¹)	Ext. optical thick. (0-h)	Ext. optical thick. (h-∞)
0	0	8.156	-3	-0.000	-0.069	-0.000	-0.237	4.70	-0.000	-0.045	1.59	-1	-0.000
1	1	7.401	-3	-0.008	-0.061	-0.108	-0.129	4.30	-0.000	-0.044	7.38	-2	-0.116
2	2	6.701	-3	-0.015	-0.054	-0.155	-0.082	3.87	-0.001	-0.044	3.56	-2	-0.171
3	3	6.054	-3	-0.021	-0.048	-0.175	-0.062	3.30	-0.001	-0.043	1.83	-2	-0.198
4	4	5.455	-3	-0.027	-0.042	-0.185	-0.053	2.98	-0.002	-0.043	1.21	-2	-0.213
5	5	4.903	-3	-0.032	-0.037	-0.190	-0.047	2.77	-0.002	-0.043	9.96	-3	-0.224
6	6	4.395	-3	-0.037	-0.032	-0.194	-0.043	2.85	-0.002	-0.042	8.04	-3	-0.233
7	7	3.928	-3	-0.041	-0.028	-0.197	-0.040	2.94	-0.002	-0.042	7.35	-3	-0.241
8	8	3.501	-3	-0.045	-0.024	-0.201	-0.037	3.01	-0.003	-0.042	7.02	-3	-0.248
9	9	3.110	-3	-0.048	-0.021	-0.204	-0.033	3.71	-0.003	-0.042	6.57	-3	-0.255
10	10	2.753	-3	-0.051	-0.018	-0.207	-0.030	4.62	-0.003	-0.041	6.22	-3	-0.261
11	11	2.429	-3	-0.053	-0.015	-0.210	-0.027	6.07	-0.004	-0.041	5.86	-3	-0.267
12	12	2.077	-3	-0.056	-0.013	-0.213	-0.025	8.20	-0.005	-0.040	5.86	-3	-0.273
13	13	1.775	-3	-0.058	-0.011	-0.215	-0.022	1.12	-0.006	-0.039	5.82	-3	-0.279
14	14	1.517	-3	-0.059	-0.010	-0.218	-0.019	1.26	-0.007	-0.038	5.46	-3	-0.284
15	15	1.297	-3	-0.061	-0.008	-0.221	-0.016	1.31	-0.008	-0.036	5.12	-3	-0.290
16	16	1.108	-3	-0.062	-0.007	-0.223	-0.014	1.36	-0.008	-0.035	4.86	-3	-0.295
17	17	9.474	-4	-0.063	-0.006	-0.226	-0.012	1.47	-0.011	-0.034	4.78	-3	-0.299
18	18	8.099	-4	-0.064	-0.005	-0.228	-0.009	1.61	-0.012	-0.032	4.71	-3	-0.304
19	19	6.924	-4	-0.064	-0.004	-0.230	-0.007	1.87	-0.014	-0.030	4.49	-3	-0.309
20	20	5.919	-4	-0.065	-0.004	-0.232	-0.005	2.16	-0.016	-0.028	4.17	-3	-0.313
21	21	5.041	-4	-0.066	-0.003	-0.233	-0.004	2.43	-0.018	-0.026	3.96	-3	-0.317
22	22	4.295	-4	-0.066	-0.003	-0.234	-0.003	2.60	-0.021	-0.024	3.80	-3	-0.321
23	23	3.662	-4	-0.067	-0.002	-0.234	-0.003	2.61	-0.024	-0.021	3.57	-3	-0.325
24	24	3.125	-4	-0.067	-0.002	-0.235	-0.002	2.55	-0.026	-0.018	3.33	-3	-0.328
25	25	2.669	-4	-0.067	-0.002	-0.235	-0.002	2.38	-0.029	-0.016	3.04	-3	-0.331
26	26	2.281	-4	-0.067	-0.001	-0.236	-0.001	2.15	-0.031	-0.014	2.72	-3	-0.334
27	27	1.951	-4	-0.068	-0.001	-0.236	-0.001	1.86	-0.033	-0.012	2.32	-3	-0.337
28	28	1.670	-4	-0.068	-0.001	-0.236	-0.001	1.62	-0.035	-0.010	1.99	-3	-0.339
29	29	1.430	-4	-0.068	-0.001	-0.237	-0.001	1.41	-0.036	-0.008	1.71	-3	-0.341
30	30	1.226	-4	-0.068	-0.001	-0.237	-0.000	1.19	-0.037	-0.007	1.43	-3	-0.342
31	31	1.051	-4	-0.068	-0.001	-0.237	-0.000	1.05	-0.039	-0.006	1.24	-3	-0.344
32	32	9.025	-5	-0.068	-0.001	-0.237	-0.000	9.00	-0.040	-0.005	1.04	-3	-0.345
33	33	7.705	-5	-0.068	-0.001	-0.237	-0.000	7.68	-0.040	-0.004	8.98	-4	-0.346
34	34	6.593	-5	-0.068	-0.000	-0.237	-0.000	6.40	-0.041	-0.003	7.67	-4	-0.347
35	35	5.635	-5	-0.068	-0.000	-0.237	-0.000	5.69	-0.042	-0.003	6.57	-4	-0.347
36	36	4.832	-5	-0.069	-0.000	-0.237	-0.000	4.77	-0.042	-0.002	5.49	-4	-0.348
37	37	4.151	-5	-0.069	-0.000	-0.237	-0.000	3.99	-0.043	-0.002	4.58	-4	-0.348
38	38	3.573	-5	-0.069	-0.000	-0.237	-0.000	3.34	-0.043	-0.002	3.84	-4	-0.349
39	39	3.080	-5	-0.069	-0.000	-0.237	-0.000	2.86	-0.043	-0.001	3.28	-4	-0.349
40	40	2.660	-5	-0.069	-0.000	-0.237	-0.000	2.44	-0.044	-0.001	2.80	-4	-0.350
41	41	2.301	-5	-0.069	-0.000	-0.237	-0.000	2.01	-0.044	-0.001	2.30	-4	-0.350
42	42	1.994	-5	-0.069	-0.000	-0.237	-0.000	1.57	-0.044	-0.001	1.82	-4	-0.350
43	43	1.730	-5	-0.069	-0.000	-0.237	-0.000	1.23	-0.044	-0.000	1.44	-4	-0.350
44	44	1.504	-5	-0.069	-0.000	-0.237	-0.000	9.82	-0.044	-0.000	1.16	-4	-0.350
45	45	1.309	-5	-0.069	-0.000	-0.237	-0.000	7.60	-0.044	-0.000	9.13	-5	-0.350
46	46	1.141	-5	-0.069	-0.000	-0.237	-0.000	5.89	-0.044	-0.000	7.19	-5	-0.350
47	47	9.963	-6	-0.069	-0.000	-0.237	-0.000	4.66	-0.044	-0.000	5.78	-5	-0.351
48	48	8.766	-6	-0.069	-0.000	-0.237	-0.000	3.68	-0.045	-0.000	4.66	-5	-0.351
49	49	7.742	-6	-0.069	-0.000	-0.237	-0.000	2.94	-0.045	-0.000	3.79	-5	-0.351
50	50	6.837	-6	-0.069	-0.000	-0.237	-0.000	2.46	-0.045	-0.000	3.20	-5	-0.351

Table 4.13 Parameters at 0.65 microns

Alt. (km)	h	Rayleigh atten. coeff. (km ⁻¹)	Rayleigh optical thick. (0-h)	Rayleigh optical thick. (h-∞)	Aerosol β _p (km ⁻¹)	Aerosol optical thick. (0-h)	Aerosol optical thick. (h-∞)	Ozone absopt. coeff. (km ⁻¹)	Ozone optical thick. (0-h)	Ozone optical thick. (h-∞)	Ext. coeff. (km ⁻²)	Ext. optical thick. (0-h)	Ext. optical thick. (h-∞)
0	0	5.893-3	.000	.050	1.42-1	.000	.224	2.21-4	.000	.021	1.48-1	.000	.295
1	1	5.349-3	.006	.044	6.25-2	.102	.122	2.02-4	.000	.021	6.80-2	.108	.187
2	2	4.842-3	.011	.039	2.70-2	.157	.073	1.82-4	.000	.021	3.20-2	.158	.157
3	3	4.374-3	.015	.034	1.13-2	.166	.058	1.55-4	.001	.020	1.59-2	.182	.115
4	4	3.942-3	.019	.030	5.99-3	.175	.050	1.40-4	.001	.020	1.04-2	.195	.100
5	5	3.543-3	.023	.027	4.51-3	.180	.044	1.37-4	.001	.020	8.19-3	.204	.091
6	6	3.176-3	.027	.023	3.18-3	.184	.041	1.34-4	.001	.020	6.49-3	.211	.084
7	7	2.838-3	.030	.020	2.96-3	.187	.038	1.34-4	.001	.020	5.93-3	.216	.078
8	8	2.529-3	.032	.018	3.05-3	.190	.035	1.41-4	.001	.020	5.72-3	.223	.072
9	9	2.247-3	.035	.015	2.92-3	.193	.032	1.74-4	.001	.020	5.34-3	.229	.066
10	10	1.989-3	.037	.013	2.85-3	.196	.029	2.17-4	.002	.019	5.06-3	.234	.061
11	11	1.755-3	.039	.011	2.67-3	.199	.026	2.85-4	.002	.019	4.71-3	.239	.056
12	12	1.501-3	.040	.010	2.80-3	.201	.023	3.85-4	.002	.019	4.69-3	.244	.052
13	13	1.282-3	.042	.008	2.59-3	.204	.021	5.24-4	.003	.018	4.39-3	.248	.047
14	14	1.096-3	.044	.007	2.53-3	.207	.018	5.93-4	.004	.017	4.22-3	.253	.043
15	15	9.369-4	.044	.006	2.38-3	.209	.015	6.16-4	.004	.016	3.93-3	.257	.039
16	16	8.008-4	.045	.005	2.26-3	.211	.013	8.49-4	.004	.016	3.70-3	.261	.035
17	17	6.846-4	.045	.004	2.24-3	.214	.011	6.88-4	.005	.016	3.61-3	.264	.031
18	18	5.852-4	.046	.004	2.17-3	.216	.009	7.56-4	.006	.015	3.51-3	.268	.028
19	19	5.003-4	.047	.003	1.82-3	.218	.007	8.80-4	.007	.014	3.21-3	.271	.024
20	20	4.277-4	.047	.003	1.34-3	.219	.005	1.02-3	.008	.013	2.78-3	.274	.021
21	21	3.642-4	.047	.002	9.71-4	.220	.004	1.14-3	.009	.012	2.48-3	.277	.019
22	22	3.103-4	.048	.002	7.31-4	.221	.003	1.22-3	.010	.011	2.26-3	.279	.016
23	23	2.646-4	.048	.002	5.59-4	.222	.002	1.23-3	.011	.010	2.05-3	.281	.014
24	24	2.258-4	.048	.001	4.43-4	.222	.002	1.40-3	.012	.009	1.87-3	.283	.012
25	25	1.928-4	.049	.001	3.73-4	.223	.002	1.12-3	.013	.007	1.68-3	.285	.010
26	26	1.648-4	.049	.001	3.25-4	.223	.001	1.01-3	.015	.006	1.50-3	.287	.009
27	27	1.409-4	.049	.001	2.59-4	.224	.001	8.74-4	.015	.005	1.26-3	.288	.007
28	28	1.206-4	.049	.001	1.91-4	.224	.001	7.63-4	.016	.005	1.07-3	.289	.006
29	29	1.034-4	.049	.001	1.45-4	.224	.001	6.83-4	.017	.004	9.13-4	.290	.005
30	30	8.856-5	.049	.001	1.12-4	.224	.000	5.60-4	.018	.003	7.61-4	.291	.004
31	31	7.537-5	.049	.001	8.58-5	.224	.000	4.92-4	.018	.003	6.53-4	.292	.004
32	32	6.521-5	.049	.000	6.51-5	.224	.000	4.23-4	.019	.002	5.54-4	.292	.003
33	33	5.567-5	.049	.000	5.03-5	.224	.000	3.61-4	.019	.002	4.67-4	.293	.003
34	34	4.757-5	.049	.000	3.86-5	.224	.000	3.01-4	.019	.002	3.87-4	.293	.002
35	35	4.071-5	.049	.000	2.96-5	.224	.000	2.67-4	.020	.001	3.38-4	.294	.002
36	36	3.491-5	.050	.000	2.26-5	.224	.000	2.24-4	.020	.001	2.81-4	.294	.001
37	37	3.000-5	.050	.000	1.73-5	.224	.000	1.87-4	.020	.001	2.45-4	.294	.001
38	38	2.582-5	.050	.000	1.33-5	.224	.000	1.57-4	.020	.001	1.96-4	.294	.001
39	39	2.226-5	.050	.000	1.02-5	.224	.000	1.35-4	.020	.001	1.67-4	.295	.001
40	40	1.922-5	.050	.000	7.78-6	.224	.000	1.15-4	.020	.000	1.42-4	.295	.001
41	41	1.663-5	.050	.000	5.97-6	.224	.000	9.42-5	.021	.000	1.17-4	.295	.000
42	42	1.441-5	.050	.000	4.57-6	.224	.000	7.38-5	.021	.000	9.28-5	.295	.000
43	43	1.250-5	.050	.000	3.50-6	.224	.000	5.77-5	.021	.000	7.37-5	.295	.000
44	44	1.087-5	.050	.000	2.58-6	.224	.000	4.61-5	.021	.000	5.97-5	.295	.000
45	45	9.459-6	.050	.000	2.05-6	.224	.000	3.57-5	.021	.000	4.72-5	.295	.000
46	46	8.246-6	.050	.000	1.57-6	.224	.000	2.77-5	.021	.000	3.75-5	.295	.000
47	47	7.199-6	.050	.000	1.20-6	.224	.000	2.19-5	.021	.000	3.03-5	.295	.000
48	48	6.334-6	.050	.000	9.26-7	.224	.000	1.73-5	.021	.000	2.46-5	.295	.000
49	49	5.594-6	.050	.000	7.06-7	.224	.000	1.38-5	.021	.000	2.01-5	.295	.000
50	50	4.940-6	.050	.000	5.41-7	.224	.000	1.15-5	.021	.000	1.70-5	.295	.000

Table 4.14 Parameters at 0.70 microns

Alt. (km)	h	Rayleigh atten. coeff. (km ⁻¹)	Rayleigh optical thick. (0-h)	Rayleigh optical thick. (h-∞)	Aerosol atten. coeff. (km ⁻¹)	Aerosol optical thick. (0-h)	Aerosol optical thick. (h-∞)	Ozone absorp. coeff. (km ⁻¹)	Ozone optical thick. (0-h)	Ozone optical thick. (h-∞)	Ext. coeff. (km ⁻¹)	Ext. optical thick. (0-h)	Ext. optical thick. (h-∞)
0	0	4.355 -3	0.00	0.037	1.35 -1	0.00	0.213	8.19 -5	0.00	0.08	1.39 -1	0.00	0.258
1	1	3.951 -3	0.04	0.033	5.94 -2	0.097	0.116	7.50 -5	0.00	0.08	6.44 -2	0.01	0.157
2	2	3.586 -3	0.08	0.029	2.56 -2	0.140	0.074	6.74 -5	0.00	0.08	2.93 -2	0.143	0.110
3	3	3.240 -3	0.11	0.026	1.08 -2	0.158	0.056	5.75 -5	0.00	0.08	1.61 -2	0.169	0.099
4	4	2.919 -3	0.14	0.022	5.69 -3	0.166	0.047	5.20 -5	0.00	0.08	8.66 -3	0.181	0.077
5	5	2.624 -3	0.17	0.020	4.29 -3	0.171	0.042	5.08 -5	0.00	0.07	6.36 -3	0.189	0.069
6	6	2.352 -3	0.20	0.017	3.02 -3	0.175	0.039	4.97 -5	0.00	0.07	5.43 -3	0.195	0.063
7	7	2.102 -3	0.22	0.015	2.81 -3	0.178	0.036	5.13 -5	0.00	0.07	4.96 -3	0.200	0.058
8	8	1.873 -3	0.24	0.013	2.90 -3	0.181	0.033	5.24 -5	0.00	0.07	4.82 -3	0.205	0.053
9	9	1.664 -3	0.26	0.011	2.78 -3	0.183	0.030	6.46 -5	0.01	0.07	4.51 -3	0.210	0.049
10	10	1.473 -3	0.27	0.010	2.71 -3	0.186	0.027	8.05 -5	0.01	0.07	4.26 -3	0.214	0.044
11	11	1.300 -3	0.29	0.008	2.54 -3	0.189	0.025	1.06 -4	0.01	0.06	3.94 -3	0.218	0.040
12	12	1.111 -3	0.30	0.007	2.67 -3	0.191	0.022	1.43 -4	0.01	0.07	3.92 -3	0.222	0.036
13	13	9.499 -4	0.31	0.006	2.46 -3	0.194	0.019	1.94 -4	0.01	0.07	3.61 -3	0.226	0.034
14	14	8.119 -4	0.32	0.005	2.41 -3	0.196	0.017	2.20 -4	0.01	0.06	3.44 -3	0.229	0.029
15	15	6.939 -4	0.32	0.004	2.26 -3	0.199	0.015	2.29 -4	0.01	0.06	3.19 -3	0.233	0.026
16	16	5.931 -4	0.33	0.004	2.15 -3	0.201	0.013	2.37 -4	0.02	0.06	2.98 -3	0.236	0.024
17	17	5.070 -4	0.34	0.003	2.13 -3	0.203	0.010	2.55 -4	0.02	0.06	2.89 -3	0.239	0.019
18	18	4.334 -4	0.34	0.003	2.06 -3	0.205	0.008	2.81 -4	0.02	0.06	2.77 -3	0.241	0.017
19	19	3.705 -4	0.35	0.002	1.73 -3	0.207	0.006	3.27 -4	0.02	0.05	2.43 -3	0.244	0.014
20	20	3.158 -4	0.35	0.002	1.27 -3	0.209	0.005	3.77 -4	0.03	0.05	1.97 -3	0.246	0.012
21	21	2.699 -4	0.35	0.002	9.23 -4	0.210	0.004	4.23 -4	0.03	0.04	1.62 -3	0.248	0.010
22	22	2.299 -4	0.35	0.001	6.95 -4	0.210	0.003	4.53 -4	0.04	0.04	1.38 -3	0.250	0.009
23	23	1.960 -4	0.36	0.001	5.31 -4	0.211	0.002	4.55 -4	0.04	0.04	1.18 -3	0.251	0.007
24	24	1.672 -4	0.36	0.001	4.21 -4	0.212	0.002	4.44 -4	0.05	0.03	1.03 -3	0.252	0.006
25	25	1.423 -4	0.36	0.001	3.55 -4	0.212	0.001	4.14 -4	0.05	0.03	9.11 -4	0.253	0.005
26	26	1.221 -4	0.36	0.001	3.09 -4	0.213	0.001	3.75 -4	0.05	0.02	8.06 -4	0.254	0.004
27	27	1.044 -4	0.36	0.001	2.37 -4	0.213	0.001	3.24 -4	0.06	0.02	6.65 -4	0.255	0.004
28	28	6.935 -5	0.36	0.001	1.81 -4	0.213	0.001	2.83 -4	0.06	0.02	5.53 -4	0.255	0.003
29	29	7.553 -5	0.36	0.001	1.39 -4	0.213	0.001	2.46 -4	0.06	0.01	4.62 -4	0.256	0.003
30	30	5.500 -5	0.36	0.001	1.07 -4	0.213	0.001	2.08 -4	0.07	0.01	3.80 -4	0.256	0.002
31	31	5.627 -5	0.36	0.001	8.16 -5	0.213	0.001	1.82 -4	0.07	0.01	3.20 -4	0.256	0.002
32	32	4.930 -5	0.37	0.001	6.25 -5	0.213	0.001	1.57 -4	0.07	0.01	2.68 -4	0.257	0.001
33	33	4.124 -5	0.37	0.001	4.78 -5	0.213	0.001	1.34 -4	0.07	0.01	2.23 -4	0.257	0.001
34	34	3.523 -5	0.37	0.001	3.67 -5	0.213	0.001	1.12 -4	0.07	0.01	1.83 -4	0.257	0.001
35	35	3.016 -5	0.37	0.001	2.81 -5	0.213	0.001	9.91 -5	0.07	0.01	1.57 -4	0.257	0.001
36	36	2.595 -5	0.37	0.001	2.15 -5	0.213	0.001	8.30 -5	0.07	0.00	1.40 -4	0.257	0.001
37	37	2.222 -5	0.37	0.001	1.65 -5	0.213	0.001	6.95 -5	0.07	0.00	1.08 -4	0.258	0.001
38	38	1.912 -5	0.37	0.001	1.26 -5	0.213	0.001	5.82 -5	0.08	0.00	9.00 -5	0.258	0.001
39	39	1.649 -5	0.37	0.001	9.56 -6	0.213	0.001	4.99 -5	0.08	0.00	7.61 -5	0.258	0.001
40	40	1.424 -5	0.37	0.001	7.40 -6	0.213	0.001	4.28 -5	0.08	0.00	6.44 -5	0.258	0.001
41	41	1.232 -5	0.37	0.001	5.57 -6	0.213	0.001	3.50 -5	0.08	0.00	5.29 -5	0.258	0.001
42	42	1.067 -5	0.37	0.001	4.34 -6	0.213	0.001	2.74 -5	0.08	0.00	4.24 -5	0.258	0.001
43	43	9.240 -6	0.37	0.001	3.32 -6	0.213	0.001	2.14 -5	0.08	0.00	3.40 -5	0.258	0.001
44	44	8.048 -6	0.37	0.001	2.55 -6	0.213	0.001	1.71 -5	0.08	0.00	2.77 -5	0.258	0.001
45	45	7.006 -6	0.37	0.001	1.95 -6	0.213	0.001	1.32 -5	0.08	0.00	2.22 -5	0.258	0.001
46	46	6.108 -6	0.37	0.001	1.50 -6	0.213	0.001	1.03 -5	0.08	0.00	1.79 -5	0.258	0.001
47	47	5.342 -6	0.37	0.001	1.14 -6	0.213	0.001	8.12 -6	0.08	0.00	1.46 -5	0.258	0.001
48	48	4.691 -6	0.37	0.001	8.60 -7	0.213	0.001	6.42 -6	0.08	0.00	1.20 -5	0.258	0.001
49	49	4.143 -6	0.37	0.001	6.72 -7	0.213	0.001	5.13 -6	0.08	0.00	9.94 -6	0.258	0.001
50	50	3.659 -6	0.37	0.001	5.14 -7	0.213	0.001	4.28 -6	0.08	0.00	8.45 -6	0.258	0.001

Table 4.15 Parameters at 0.80 microns

Alt. (km)	h	Rayleigh atten. coeff. (km ⁻¹)	Rayleigh optical thick. (0-h)	Rayleigh optical thick. (h-∞)	Aerosol atten. coeff. (km ⁻¹)	Aerosol optical thick. (0-h)	Aerosol optical thick. (h-∞)	Ozone absorp. coeff. (km ⁻¹)	Ozone optical thick. (0-h)	Ozone optical thick. (h-∞)	Ext. coeff. (km ⁻¹)	Ext. optical thick. (0-h)	Ext. optical thick. (h-∞)
0	0	2.544	-3	-0.00	1.27	-1	.201	3.56	-5	.000	1.30	-1	.000
1	1	2.309	-3	-0.02	5.59	-2	.109	3.26	-5	.000	5.22	-2	.094
2	2	2.091	-3	-0.05	2.41	-2	.069	2.93	-5	.000	2.62	-2	.136
3	3	1.883	-3	-0.07	1.01	-2	.052	2.50	-5	.000	1.20	-2	.155
4	4	1.702	-3	-0.08	5.35	-3	.156	2.26	-5	.000	7.08	-3	.165
5	5	1.540	-3	-0.10	4.04	-3	.161	2.21	-5	.000	5.59	-3	.171
6	6	1.371	-3	-0.11	2.65	-3	.164	2.16	-5	.000	4.24	-3	.176
7	7	1.225	-3	-0.13	2.54	-3	.167	2.23	-5	.000	3.89	-3	.180
8	8	1.092	-3	-0.14	2.72	-3	.170	2.28	-5	.000	3.84	-3	.184
9	9	9.702	-4	-0.15	2.61	-3	.173	2.81	-5	.000	3.61	-3	.188
10	10	8.539	-4	-0.16	2.55	-3	.175	3.50	-5	.000	3.44	-3	.191
11	11	7.577	-4	-0.17	2.49	-3	.178	4.60	-5	.000	3.19	-3	.195
12	12	6.479	-4	-0.17	2.51	-3	.180	6.21	-5	.000	3.22	-3	.198
13	13	5.538	-4	-0.18	2.31	-3	.182	8.45	-5	.000	2.95	-3	.201
14	14	4.733	-4	-0.18	2.27	-3	.185	9.57	-5	.001	2.84	-3	.204
15	15	4.045	-4	-0.19	2.13	-3	.187	9.74	-5	.001	2.63	-3	.206
16	16	3.453	-4	-0.19	2.03	-3	.189	1.03	-4	.001	2.47	-3	.209
17	17	2.956	-4	-0.20	2.00	-3	.191	1.11	-4	.001	2.41	-3	.211
18	18	2.527	-4	-0.20	1.94	-3	.193	1.22	-4	.001	2.31	-3	.214
19	19	2.160	-4	-0.20	1.83	-3	.195	1.42	-4	.001	1.99	-3	.216
20	20	1.847	-4	-0.20	1.20	-3	.196	1.64	-4	.001	1.55	-3	.218
21	21	1.573	-4	-0.20	8.08	-4	.197	1.34	-4	.001	1.21	-3	.219
22	22	1.340	-4	-0.21	6.53	-4	.198	1.97	-4	.002	9.84	-4	.220
23	23	1.143	-4	-0.21	5.00	-4	.199	1.98	-4	.002	8.12	-4	.221
24	24	9.750	-5	-0.21	3.36	-4	.199	1.93	-4	.002	0.87	-4	.222
25	25	8.226	-5	-0.21	3.34	-4	.199	1.80	-4	.002	5.97	-4	.223
26	26	7.115	-5	-0.21	2.91	-4	.200	1.63	-4	.002	5.25	-4	.223
27	27	6.036	-5	-0.21	2.23	-4	.200	1.41	-4	.002	4.23	-4	.224
28	28	5.209	-5	-0.21	1.70	-4	.200	1.23	-4	.003	3.45	-4	.224
29	29	4.451	-5	-0.21	1.31	-4	.200	1.07	-4	.003	2.83	-4	.224
30	30	3.824	-5	-0.21	1.00	-4	.200	9.03	-5	.003	2.29	-4	.225
31	31	3.230	-5	-0.21	7.68	-5	.200	7.93	-5	.003	1.89	-4	.225
32	32	2.815	-5	-0.21	5.88	-5	.201	6.82	-5	.003	1.55	-4	.225
33	33	2.464	-5	-0.21	4.50	-5	.201	5.82	-5	.003	1.27	-4	.225
34	34	2.054	-5	-0.21	3.45	-5	.201	4.85	-5	.003	1.04	-4	.225
35	35	1.758	-5	-0.21	2.64	-5	.201	4.31	-5	.003	8.71	-5	.225
36	36	1.508	-5	-0.21	2.04	-5	.201	3.61	-5	.003	7.14	-5	.225
37	37	1.295	-5	-0.21	1.55	-5	.201	3.02	-5	.003	5.87	-5	.225
38	38	1.115	-5	-0.21	1.19	-5	.201	2.53	-5	.003	4.83	-5	.225
39	39	9.610	-6	-0.21	9.08	-5	.201	2.17	-5	.003	4.04	-5	.225
40	40	8.300	-6	-0.21	6.36	-6	.201	1.85	-5	.003	3.39	-5	.226
41	41	7.179	-6	-0.21	5.34	-6	.201	1.52	-5	.003	2.77	-5	.226
42	42	6.221	-6	-0.21	4.08	-6	.201	1.19	-5	.003	2.22	-5	.226
43	43	5.398	-6	-0.21	3.13	-6	.201	9.20	-6	.003	1.78	-5	.226
44	44	4.692	-6	-0.21	2.40	-6	.201	7.44	-6	.003	1.45	-5	.226
45	45	4.084	-6	-0.21	1.83	-6	.201	5.76	-6	.003	1.17	-5	.226
46	46	3.561	-6	-0.21	1.41	-6	.201	4.45	-6	.003	9.43	-6	.226
47	47	3.106	-6	-0.21	1.08	-6	.201	3.53	-6	.003	7.72	-6	.226
48	48	2.735	-6	-0.21	8.28	-7	.201	2.79	-6	.003	6.35	-6	.226
49	49	2.415	-6	-0.21	6.32	-7	.201	2.23	-6	.003	5.28	-6	.226
50	50	2.133	-6	-0.21	4.84	-7	.201	1.86	-6	.003	4.48	-6	.226

Table 4.16 Parameters at 0.80 microns

Alt. (km)	h	Rayleigh atten. coeff. (km ⁻¹)	Rayleigh optical thick. (0-h)	Rayleigh optical thick. (h-∞)	Aerosol atten. coeff. (km ⁻¹)	Aerosol optical thick. (0-h)	Aerosol optical thick. (h-∞)	Ozone absorp. coeff. (km ⁻¹)	Ozone optical thick. (0-h)	Ozone optical thick. (h-∞)	Ext. coeff. (km ⁻¹)	Ext. optical thick. (0-h)	Ext. optical thick. (h-∞)
0	0	1.593 -3	0.00	0.15	1.20 -1	0.00	0.19	0.	0.00	0.00	1.22 -1	0.00	0.00
1	1	1.236 -3	0.02	0.12	5.29 -2	0.06	0.10	0.	0.00	0.00	5.42 -2	0.08	0.11
2	2	1.100 -3	0.03	0.10	2.28 -2	0.14	0.06	0.	0.00	0.00	2.41 -2	0.17	0.07
3	3	1.175 -3	0.04	0.09	9.57 -3	0.14	0.09	0.	0.00	0.00	1.07 -2	0.14	0.09
4	4	1.059 -3	0.05	0.08	5.06 -3	0.14	0.09	0.	0.00	0.00	6.12 -3	0.15	0.05
5	5	9.514 -4	0.06	0.07	3.51 -3	0.15	0.08	0.	0.00	0.00	4.76 -3	0.15	0.05
6	6	8.528 -4	0.07	0.06	2.59 -3	0.15	0.08	0.	0.00	0.00	3.54 -3	0.16	0.04
7	7	7.622 -4	0.08	0.05	2.50 -3	0.15	0.08	0.	0.00	0.00	3.46 -3	0.16	0.03
8	8	6.733 -4	0.09	0.05	2.57 -3	0.16	0.09	0.	0.00	0.00	3.25 -3	0.16	0.03
9	9	5.034 -4	0.09	0.04	2.47 -3	0.15	0.09	0.	0.00	0.00	3.07 -3	0.17	0.03
10	10	5.342 -4	0.10	0.04	2.41 -3	0.15	0.09	0.	0.00	0.00	2.94 -3	0.17	0.04
11	11	4.713 -4	0.10	0.03	2.26 -3	0.16	0.09	0.	0.00	0.00	2.73 -3	0.17	0.05
12	12	4.030 -4	0.11	0.03	2.37 -3	0.17	0.09	0.	0.00	0.00	2.77 -3	0.18	0.05
13	13	3.444 -4	0.11	0.02	2.19 -3	0.17	0.09	0.	0.00	0.00	2.53 -3	0.18	0.07
14	14	2.944 -4	0.11	0.02	2.14 -3	0.17	0.09	0.	0.00	0.00	2.44 -3	0.18	0.17
15	15	2.515 -4	0.12	0.02	2.31 -3	0.17	0.13	0.	0.00	0.00	2.26 -3	0.18	0.15
16	16	2.151 -4	0.12	0.01	1.91 -3	0.17	0.13	0.	0.00	0.00	2.13 -3	0.19	0.13
17	17	1.838 -4	0.12	0.01	1.83 -3	0.19	0.09	0.	0.00	0.00	2.07 -3	0.19	0.10
18	18	1.572 -4	0.12	0.01	1.34 -3	0.12	0.07	0.	0.00	0.00	1.99 -3	0.19	0.08
19	19	1.344 -4	0.13	0.01	1.34 -3	0.14	0.06	0.	0.00	0.00	1.88 -3	0.19	0.07
20	20	1.143 -4	0.13	0.01	1.13 -3	0.18	0.04	0.	0.00	0.00	1.25 -3	0.19	0.05
21	21	9.781 -5	0.13	0.01	8.20 -4	0.18	0.03	0.	0.00	0.00	9.18 -4	0.19	0.04
22	22	8.334 -5	0.13	0.01	6.17 -4	0.18	0.03	0.	0.00	0.00	7.01 -4	0.20	0.03
23	23	7.105 -5	0.13	0.00	4.72 -4	0.18	0.02	0.	0.00	0.00	5.43 -4	0.20	0.03
24	24	6.054 -5	0.13	0.00	3.74 -4	0.18	0.02	0.	0.00	0.00	4.35 -4	0.20	0.02
25	25	5.175 -5	0.13	0.00	3.15 -4	0.18	0.01	0.	0.00	0.00	3.67 -4	0.20	0.02
26	26	4.425 -5	0.13	0.00	2.75 -4	0.18	0.01	0.	0.00	0.00	3.19 -4	0.20	0.01
27	27	3.785 -5	0.13	0.00	2.10 -4	0.18	0.01	0.	0.00	0.00	2.48 -4	0.20	0.01
28	28	3.240 -5	0.13	0.00	1.51 -4	0.18	0.01	0.	0.00	0.00	1.93 -4	0.20	0.01
29	29	2.775 -5	0.13	0.00	1.24 -4	0.18	0.00	0.	0.00	0.00	1.52 -4	0.20	0.01
30	30	2.378 -5	0.13	0.00	9.59 -5	0.18	0.00	0.	0.00	0.00	1.19 -4	0.20	0.01
31	31	2.040 -5	0.13	0.00	7.25 -5	0.19	0.00	0.	0.00	0.00	9.29 -5	0.20	0.00
32	32	1.751 -5	0.13	0.00	5.55 -5	0.19	0.00	0.	0.00	0.00	7.30 -5	0.20	0.00
33	33	1.495 -5	0.13	0.00	4.25 -5	0.19	0.00	0.	0.00	0.00	5.75 -5	0.20	0.00
34	34	1.277 -5	0.13	0.00	3.26 -5	0.19	0.00	0.	0.00	0.00	4.54 -5	0.20	0.00
35	35	1.093 -5	0.13	0.00	2.50 -5	0.19	0.00	0.	0.00	0.00	3.59 -5	0.20	0.00
36	36	9.376 -6	0.13	0.00	1.91 -5	0.19	0.00	0.	0.00	0.00	2.85 -5	0.20	0.00
37	37	8.055 -6	0.13	0.00	1.47 -5	0.19	0.00	0.	0.00	0.00	2.27 -5	0.20	0.00
38	38	6.913 -6	0.13	0.00	1.12 -5	0.19	0.00	0.	0.00	0.00	1.82 -5	0.20	0.00
39	39	5.977 -6	0.13	0.00	8.58 -6	0.19	0.00	0.	0.00	0.00	1.45 -5	0.20	0.00
40	40	5.162 -6	0.13	0.00	6.58 -6	0.19	0.00	0.	0.00	0.00	1.17 -5	0.20	0.00
41	41	4.465 -6	0.13	0.00	5.04 -6	0.19	0.00	0.	0.00	0.00	9.51 -6	0.20	0.00
42	42	3.857 -6	0.13	0.00	3.86 -6	0.19	0.00	0.	0.00	0.00	7.73 -6	0.20	0.00
43	43	3.353 -6	0.13	0.00	2.95 -6	0.19	0.00	0.	0.00	0.00	6.31 -6	0.20	0.00
44	44	2.919 -6	0.13	0.00	2.26 -6	0.19	0.00	0.	0.00	0.00	5.18 -6	0.20	0.00
45	45	2.540 -6	0.13	0.00	1.73 -6	0.19	0.00	0.	0.00	0.00	4.27 -6	0.20	0.00
46	46	2.214 -6	0.13	0.00	1.33 -6	0.19	0.00	0.	0.00	0.00	3.54 -6	0.20	0.00
47	47	1.933 -6	0.13	0.00	1.02 -5	0.19	0.00	0.	0.00	0.00	2.95 -6	0.20	0.00
48	48	1.701 -6	0.13	0.00	7.92 -7	0.19	0.00	0.	0.00	0.00	2.48 -6	0.20	0.00
49	49	1.502 -6	0.13	0.00	5.37 -7	0.19	0.00	0.	0.00	0.00	2.10 -6	0.20	0.00
50	50	1.327 -6	0.13	0.00	4.57 -7	0.19	0.00	0.	0.00	0.00	1.78 -6	0.20	0.00

Table 4.17 Parameters at 1.06 microns

Alt. (km)	h	Rayleigh atten. coeff. (km ⁻¹)	Rayleigh optical thick. (0-h)	Rayleigh optical thick. (h-∞)	Aerosol atten. coeff. (km ⁻¹)	Aerosol optical thick. (0-h)	Aerosol optical thick. (h-∞)	Ozone absorp. coeff. (km ⁻¹)	Ozone optical thick. (0-h)	Ozone optical thick. (h-∞)	Ext. coeff. (km ⁻¹)	Ext. optical thick. (0-h)	Ext. optical thick. (h-∞)
0	0	5.192	0.000	0.007	1.13	0.000	0.179	0.	0.000	0.000	1.14	0.000	0.186
1	1	7.434	0.001	0.006	4.97	0.081	0.097	0.	0.000	0.000	5.04	0.082	0.105
2	2	7.731	0.001	0.005	2.15	0.117	0.062	0.	0.000	0.000	2.21	0.118	0.067
3	3	5.081	0.002	0.005	9.01	0.142	0.045	0.	0.000	0.000	9.02	0.134	0.021
4	4	5.480	0.003	0.004	4.76	0.139	0.040	0.	0.000	0.000	5.31	0.142	0.044
5	5	4.925	0.003	0.004	3.59	0.143	0.035	0.	0.000	0.000	4.08	0.146	0.039
6	6	4.415	0.004	0.003	2.53	0.146	0.032	0.	0.000	0.000	2.97	0.150	0.036
7	7	3.945	0.004	0.003	2.35	0.163	0.030	0.	0.000	0.000	2.75	0.153	0.033
8	8	3.516	0.004	0.002	2.42	0.151	0.028	0.	0.000	0.000	2.78	0.155	0.030
9	9	3.123	0.005	0.002	2.32	0.153	0.025	0.	0.000	0.000	2.64	0.158	0.027
10	10	2.765	0.005	0.002	2.27	0.156	0.023	0.	0.000	0.000	2.54	0.161	0.025
11	11	2.440	0.005	0.002	2.12	0.158	0.021	0.	0.000	0.000	2.37	0.163	0.022
12	12	2.036	0.006	0.001	2.25	0.160	0.018	0.	0.000	0.000	2.44	0.166	0.020
13	13	1.733	0.006	0.001	2.06	0.162	0.016	0.	0.000	0.000	2.24	0.168	0.017
14	14	1.524	0.006	0.001	2.02	0.164	0.014	0.	0.000	0.000	2.17	0.170	0.015
15	15	1.302	0.006	0.001	1.90	0.166	0.012	0.	0.000	0.000	2.03	0.172	0.013
16	16	1.113	0.006	0.001	1.80	0.168	0.010	0.	0.000	0.000	1.91	0.174	0.011
17	17	9.517	0.006	0.001	1.73	0.170	0.009	0.	0.000	0.000	1.88	0.176	0.009
18	18	8.135	0.006	0.001	1.72	0.172	0.007	0.	0.000	0.000	1.80	0.176	0.007
19	19	6.935	0.006	0.000	1.65	0.173	0.005	0.	0.000	0.000	1.72	0.180	0.006
20	20	5.945	0.007	0.000	1.07	0.175	0.004	0.	0.000	0.000	1.15	0.181	0.004
21	21	5.053	0.007	0.000	7.72	0.175	0.003	0.	0.000	0.000	8.25	0.182	0.003
22	22	4.314	0.007	0.000	5.91	0.176	0.002	0.	0.000	0.000	6.25	0.183	0.003
23	23	3.673	0.007	0.000	4.65	0.177	0.002	0.	0.000	0.000	4.82	0.183	0.002
24	24	3.143	0.007	0.000	3.53	0.177	0.002	0.	0.000	0.000	3.84	0.184	0.002
25	25	2.691	0.007	0.000	2.97	0.177	0.001	0.	0.000	0.000	3.25	0.184	0.001
26	26	2.291	0.007	0.000	2.59	0.178	0.001	0.	0.000	0.000	2.82	0.184	0.001
27	27	1.953	0.007	0.000	1.38	0.178	0.001	0.	0.000	0.000	2.18	0.185	0.001
28	28	1.677	0.007	0.000	1.52	0.178	0.001	0.	0.000	0.000	1.68	0.185	0.001
29	29	1.436	0.007	0.000	1.17	0.178	0.000	0.	0.000	0.000	1.31	0.185	0.001
30	30	1.231	0.007	0.000	8.74	0.178	0.000	0.	0.000	0.000	1.02	0.185	0.000
31	31	1.056	0.007	0.000	6.63	0.178	0.000	0.	0.000	0.000	7.83	0.185	0.000
32	32	9.055	0.007	0.000	5.23	0.178	0.000	0.	0.000	0.000	6.13	0.185	0.000
33	33	7.750	0.007	0.000	4.01	0.178	0.000	0.	0.000	0.000	4.78	0.185	0.000
34	34	6.612	0.007	0.000	3.07	0.179	0.000	0.	0.000	0.000	3.73	0.185	0.000
35	35	5.663	0.007	0.000	2.35	0.179	0.000	0.	0.000	0.000	2.92	0.185	0.000
36	36	4.854	0.007	0.000	1.80	0.179	0.000	0.	0.000	0.000	2.29	0.185	0.000
37	37	4.170	0.007	0.000	1.38	0.179	0.000	0.	0.000	0.000	1.80	0.185	0.000
38	38	3.587	0.007	0.000	1.06	0.179	0.000	0.	0.000	0.000	1.42	0.185	0.000
39	39	3.094	0.007	0.000	8.08	0.179	0.000	0.	0.000	0.000	1.12	0.186	0.000
40	40	2.672	0.007	0.000	6.19	0.179	0.000	0.	0.000	0.000	6.87	0.186	0.000
41	41	2.311	0.007	0.000	4.75	0.179	0.000	0.	0.000	0.000	7.05	0.186	0.000
42	42	2.003	0.007	0.000	3.63	0.179	0.000	0.	0.000	0.000	5.54	0.186	0.000
43	43	1.736	0.007	0.000	2.78	0.179	0.000	0.	0.000	0.000	4.52	0.186	0.000
44	44	1.511	0.007	0.000	2.13	0.179	0.000	0.	0.000	0.000	3.84	0.186	0.000
45	45	1.315	0.007	0.000	1.63	0.179	0.000	0.	0.000	0.000	2.95	0.186	0.000
46	46	1.145	0.007	0.000	1.25	0.179	0.000	0.	0.000	0.000	2.40	0.186	0.000
47	47	1.001	0.007	0.000	9.56	0.179	0.000	0.	0.000	0.000	1.95	0.186	0.000
48	48	8.835	0.007	0.000	7.37	0.179	0.000	0.	0.000	0.000	1.62	0.186	0.000
49	49	7.776	0.007	0.000	5.52	0.179	0.000	0.	0.000	0.000	1.34	0.186	0.000
50	50	6.857	0.007	0.000	4.31	0.179	0.000	0.	0.000	0.000	1.12	0.186	0.000

Table 4.18 Parameters at 1.26 microns

Alt. (km)	h	Rayleigh atten. coeff. (km ⁻¹)	Rayleigh optical thick. (0-h)	Rayleigh optical thick. (h-∞)	Aerosol atten. coeff. (km ⁻¹)	Aerosol optical thick. (0-h)	Aerosol optical thick. (h-∞)	Ozone absorp. coeff. (km ⁻¹)	Ozone optical thick. (0-h)	Ozone optical thick. (h-∞)	Ext. coeff. (km ⁻¹)	Ext. optical thick. (0-h)	Ext. optical thick. (h-∞)
0	0	4.091	4	0.03	1.08	0.00	0.00	0	0.00	0.00	1.08	0.00	0.174
1	1	3.713	4	0.03	4.75	0.078	0.00	0	0.00	0.00	4.75	0.078	0.096
2	2	3.352	4	0.01	2.05	0.112	0.00	0	0.00	0.00	2.05	0.112	0.062
3	3	3.037	4	0.02	8.31	0.125	0.00	0	0.00	0.00	8.31	0.125	0.047
4	4	2.737	4	0.02	4.55	0.133	0.00	0	0.00	0.00	4.55	0.133	0.040
5	5	2.450	4	0.02	3.63	0.137	0.00	0	0.00	0.00	3.63	0.137	0.036
6	6	2.195	4	0.02	2.64	0.140	0.00	0	0.00	0.00	2.64	0.140	0.033
7	7	1.971	4	0.02	2.25	0.142	0.00	0	0.00	0.00	2.25	0.142	0.030
8	8	1.755	4	0.02	2.32	0.144	0.00	0	0.00	0.00	2.32	0.144	0.026
9	9	1.560	4	0.02	2.22	0.147	0.00	0	0.00	0.00	2.22	0.147	0.025
10	10	1.381	4	0.03	2.17	0.149	0.00	0	0.00	0.00	2.17	0.149	0.023
11	11	1.213	4	0.03	2.03	0.151	0.00	0	0.00	0.00	2.03	0.151	0.021
12	12	1.042	4	0.03	2.13	0.153	0.00	0	0.00	0.00	2.13	0.153	0.018
13	13	0.902	5	0.03	1.97	0.155	0.00	0	0.00	0.00	1.97	0.155	0.016
14	14	0.780	5	0.03	1.83	0.157	0.00	0	0.00	0.00	1.83	0.157	0.014
15	15	0.680	5	0.03	1.81	0.159	0.00	0	0.00	0.00	1.81	0.159	0.012
16	16	0.590	5	0.03	1.72	0.161	0.00	0	0.00	0.00	1.72	0.161	0.010
17	17	0.513	5	0.03	1.65	0.162	0.00	0	0.00	0.00	1.65	0.162	0.009
18	18	0.453	5	0.03	1.55	0.164	0.00	0	0.00	0.00	1.55	0.164	0.007
19	19	0.403	5	0.03	1.45	0.166	0.00	0	0.00	0.00	1.45	0.166	0.005
20	20	0.369	5	0.03	1.32	0.167	0.00	0	0.00	0.00	1.32	0.167	0.004
21	21	0.328	5	0.03	1.26	0.168	0.00	0	0.00	0.00	1.26	0.168	0.003
22	22	0.295	5	0.03	1.18	0.169	0.00	0	0.00	0.00	1.18	0.169	0.002
23	23	0.267	5	0.03	1.09	0.169	0.00	0	0.00	0.00	1.09	0.169	0.002
24	24	0.243	5	0.03	1.01	0.169	0.00	0	0.00	0.00	1.01	0.169	0.001
25	25	0.221	5	0.03	0.94	0.170	0.00	0	0.00	0.00	0.94	0.170	0.001
26	26	0.201	5	0.03	0.87	0.170	0.00	0	0.00	0.00	0.87	0.170	0.001
27	27	0.183	5	0.03	0.81	0.170	0.00	0	0.00	0.00	0.81	0.170	0.001
28	28	0.167	5	0.03	0.75	0.170	0.00	0	0.00	0.00	0.75	0.170	0.001
29	29	0.153	5	0.03	0.70	0.170	0.00	0	0.00	0.00	0.70	0.170	0.000
30	30	0.140	5	0.03	0.65	0.170	0.00	0	0.00	0.00	0.65	0.170	0.000
31	31	0.128	5	0.03	0.61	0.170	0.00	0	0.00	0.00	0.61	0.170	0.000
32	32	0.117	5	0.03	0.57	0.171	0.00	0	0.00	0.00	0.57	0.171	0.000
33	33	0.107	5	0.03	0.53	0.171	0.00	0	0.00	0.00	0.53	0.171	0.000
34	34	0.100	5	0.03	0.50	0.171	0.00	0	0.00	0.00	0.50	0.171	0.000
35	35	0.092	5	0.03	0.47	0.171	0.00	0	0.00	0.00	0.47	0.171	0.000
36	36	0.086	5	0.03	0.44	0.171	0.00	0	0.00	0.00	0.44	0.171	0.000
37	37	0.081	5	0.03	0.42	0.171	0.00	0	0.00	0.00	0.42	0.171	0.000
38	38	0.076	5	0.03	0.40	0.171	0.00	0	0.00	0.00	0.40	0.171	0.000
39	39	0.072	5	0.03	0.38	0.171	0.00	0	0.00	0.00	0.38	0.171	0.000
40	40	0.068	5	0.03	0.36	0.171	0.00	0	0.00	0.00	0.36	0.171	0.000
41	41	0.065	5	0.03	0.34	0.171	0.00	0	0.00	0.00	0.34	0.171	0.000
42	42	0.062	5	0.03	0.32	0.171	0.00	0	0.00	0.00	0.32	0.171	0.000
43	43	0.060	5	0.03	0.30	0.171	0.00	0	0.00	0.00	0.30	0.171	0.000
44	44	0.058	5	0.03	0.28	0.171	0.00	0	0.00	0.00	0.28	0.171	0.000
45	45	0.056	5	0.03	0.26	0.171	0.00	0	0.00	0.00	0.26	0.171	0.000
46	46	0.054	5	0.03	0.24	0.171	0.00	0	0.00	0.00	0.24	0.171	0.000
47	47	0.052	5	0.03	0.22	0.171	0.00	0	0.00	0.00	0.22	0.171	0.000
48	48	0.050	5	0.03	0.20	0.171	0.00	0	0.00	0.00	0.20	0.171	0.000
49	49	0.048	5	0.03	0.18	0.171	0.00	0	0.00	0.00	0.18	0.171	0.000
50	50	0.046	5	0.03	0.17	0.171	0.00	0	0.00	0.00	0.17	0.171	0.000

Table 4.19 Parameters at 1.67 microns

Alt (km)	h	Rayleigh atten. coeff. (km ⁻¹)	Rayleigh optical thick. (0-h)	Rayleigh optical thick. (h-∞)	Aerosol atten. coeff. (km ⁻¹)	Aerosol optical thick. (0-h)	Aerosol optical thick. (h-∞)	Ozone absorp. coeff. (km ⁻¹)	Ozone optical thick. (0-h)	Ozone optical thick. (h-∞)	Ext. coeff. (km ⁻¹)	Ext. optical thick. (0-h)	Ext. optical thick. (h-∞)
0	0	1.422 -4	.000	.001	5.30 -2	.000	.155	0.	.000	.000	9.81 -2	.000	.156
1	1	1.199 -4	.000	.001	4.31 -2	.071	.084	0.	.000	.000	4.32 -2	.071	.085
2	2	1.085 -4	.000	.001	1.35 -2	.101	.054	0.	.000	.000	1.87 -2	.102	.054
3	3	9.710 -5	.000	.001	7.42 -3	.115	.040	0.	.000	.000	7.91 -3	.115	.041
4	4	8.841 -5	.000	.001	4.13 -3	.121	.034	0.	.000	.000	4.22 -3	.121	.035
5	5	7.965 -5	.001	.001	3.11 -3	.124	.031	0.	.000	.000	3.19 -3	.125	.031
6	6	7.122 -5	.001	.001	2.20 -3	.127	.028	0.	.000	.000	2.27 -3	.127	.029
7	7	6.365 -5	.001	.001	1.29 -3	.129	.026	0.	.000	.000	2.10 -3	.130	.026
8	8	5.675 -5	.001	.000	4.10 -3	.131	.024	0.	.000	.000	2.15 -3	.132	.024
9	9	5.039 -5	.001	.000	2.02 -3	.133	.022	0.	.000	.000	2.07 -3	.134	.022
10	10	4.452 -5	.001	.000	1.97 -3	.135	.020	0.	.000	.000	2.01 -3	.136	.020
11	11	3.915 -5	.001	.000	1.34 -3	.137	.018	0.	.000	.000	1.83 -3	.138	.018
12	12	3.365 -5	.001	.000	1.34 -3	.139	.016	0.	.000	.000	1.87 -3	.140	.016
13	13	2.875 -5	.001	.000	1.79 -3	.141	.014	0.	.000	.000	1.82 -3	.142	.014
14	14	2.459 -5	.001	.000	1.75 -3	.143	.012	0.	.000	.000	1.77 -3	.143	.012
15	15	2.101 -5	.001	.000	1.34 -3	.144	.011	0.	.000	.000	1.83 -3	.145	.011
16	16	1.796 -5	.001	.000	1.55 -3	.146	.009	0.	.000	.000	1.53 -3	.147	.009
17	17	1.535 -5	.001	.000	1.54 -3	.147	.008	0.	.000	.000	1.26 -3	.148	.008
18	18	1.313 -5	.001	.000	1.49 -3	.149	.006	0.	.000	.000	1.51 -3	.150	.006
19	19	1.122 -5	.001	.000	1.25 -3	.150	.005	0.	.000	.000	1.27 -3	.151	.005
20	20	9.534 -6	.001	.000	9.24 -4	.151	.004	0.	.000	.000	9.34 -4	.152	.004
21	21	8.154 -6	.001	.000	8.70 -4	.152	.003	0.	.000	.000	6.73 -4	.153	.003
22	22	6.851 -6	.001	.000	5.04 -4	.153	.002	0.	.000	.000	5.11 -4	.154	.002
23	23	5.935 -6	.001	.000	3.36 -4	.154	.001	0.	.000	.000	3.92 -4	.154	.001
24	24	5.054 -6	.001	.000	3.06 -4	.154	.001	0.	.000	.000	2.62 -4	.155	.001
25	25	4.325 -6	.001	.000	2.57 -4	.154	.001	0.	.000	.000	2.28 -4	.155	.001
26	26	3.595 -6	.001	.000	2.25 -4	.154	.001	0.	.000	.000	1.75 -4	.155	.001
27	27	3.131 -6	.001	.000	1.72 -4	.154	.001	0.	.000	.000	1.34 -4	.155	.001
28	28	2.705 -6	.001	.000	1.31 -4	.154	.000	0.	.000	.000	1.03 -4	.156	.000
29	29	2.317 -6	.001	.000	1.01 -4	.155	.000	0.	.000	.000	7.95 -5	.156	.000
30	30	1.835 -6	.001	.000	7.75 -5	.155	.000	0.	.000	.000	6.09 -5	.156	.000
31	31	1.705 -6	.001	.000	5.92 -5	.155	.000	0.	.000	.000	4.63 -5	.156	.000
32	32	1.454 -6	.001	.000	4.53 -5	.155	.000	0.	.000	.000	3.60 -5	.156	.000
33	33	1.240 -6	.001	.000	3.47 -5	.155	.000	0.	.000	.000	2.77 -5	.156	.000
34	34	1.077 -6	.001	.000	2.56 -5	.155	.000	0.	.000	.000	2.13 -5	.156	.000
35	35	9.142 -7	.001	.000	2.04 -5	.155	.000	0.	.000	.000	1.54 -5	.156	.000
36	36	7.831 -7	.001	.000	1.56 -5	.155	.000	0.	.000	.000	1.20 -5	.156	.000
37	37	6.728 -7	.001	.000	1.20 -5	.155	.000	0.	.000	.000	9.76 -6	.156	.000
38	38	5.790 -7	.001	.000	9.18 -6	.155	.000	0.	.000	.000	7.51 -6	.156	.000
39	39	4.932 -7	.001	.000	7.01 -6	.155	.000	0.	.000	.000	5.80 -6	.156	.000
40	40	4.311 -7	.001	.000	5.37 -6	.155	.000	0.	.000	.000	4.49 -6	.156	.000
41	41	3.729 -7	.001	.000	4.12 -6	.155	.000	0.	.000	.000	3.47 -6	.156	.000
42	42	3.231 -7	.001	.000	3.15 -6	.155	.000	0.	.000	.000	2.69 -6	.156	.000
43	43	2.804 -7	.001	.000	2.41 -6	.155	.000	0.	.000	.000	2.06 -6	.156	.000
44	44	2.437 -7	.001	.000	1.95 -6	.155	.000	0.	.000	.000	1.53 -6	.156	.000
45	45	2.122 -7	.001	.000	1.41 -6	.155	.000	0.	.000	.000	1.27 -6	.156	.000
46	46	1.849 -7	.001	.000	1.09 -6	.155	.000	0.	.000	.000	9.93 -7	.156	.000
47	47	1.615 -7	.001	.000	8.31 -7	.155	.000	0.	.000	.000	7.81 -7	.156	.000
48	48	1.421 -7	.001	.000	6.39 -7	.155	.000	0.	.000	.000	6.13 -7	.156	.000
49	49	1.255 -7	.001	.000	4.84 -7	.155	.000	0.	.000	.000	4.94 -7	.156	.000
50	50	1.113 -7	.001	.000	3.73 -7	.155	.000	0.	.000	.000		.156	

Table 4.20 Parameters at 2.17 microns

Alt. (km)	h	Rayleigh atten. coeff. (km ⁻¹)	Rayleigh optical thick. (0-h)	Rayleigh optical thick. (h-∞)	Aerosol atten. coeff. (km ⁻¹)	Aerosol optical thick. (0-h)	Aerosol optical thick. (h-∞)	Ozone absorp. coeff. (km ⁻¹)	Ozone optical thick. (0-h)	Ozone optical thick. (h-∞)	Ext. coeff. (km ⁻¹)	Ext. optical thick. (0-h)	Ext. optical thick. (h-∞)
0	0	4.629	0.00	0.00	8.50	0.00	0.00	0.00	0.00	0.00	8.50	0.00	0.00
1	1	4.200	0.00	0.00	3.74	0.00	0.00	0.00	0.00	0.00	3.74	0.00	0.00
2	2	3.803	0.00	0.00	1.51	0.00	0.00	0.00	0.00	0.00	1.51	0.00	0.00
3	3	3.436	0.00	0.00	0.78	0.00	0.00	0.00	0.00	0.00	0.78	0.00	0.00
4	4	3.096	0.00	0.00	0.53	0.00	0.00	0.00	0.00	0.00	0.53	0.00	0.00
5	5	2.783	0.00	0.00	0.30	0.00	0.00	0.00	0.00	0.00	0.30	0.00	0.00
6	6	2.494	0.00	0.00	0.16	0.00	0.00	0.00	0.00	0.00	0.16	0.00	0.00
7	7	2.223	0.00	0.00	0.10	0.00	0.00	0.00	0.00	0.00	0.10	0.00	0.00
8	8	1.977	0.00	0.00	0.06	0.00	0.00	0.00	0.00	0.00	0.06	0.00	0.00
9	9	1.765	0.00	0.00	0.04	0.00	0.00	0.00	0.00	0.00	0.04	0.00	0.00
10	10	1.582	0.00	0.00	0.03	0.00	0.00	0.00	0.00	0.00	0.03	0.00	0.00
11	11	1.437	0.00	0.00	0.02	0.00	0.00	0.00	0.00	0.00	0.02	0.00	0.00
12	12	1.273	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
13	13	1.107	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
14	14	0.960	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
15	15	0.833	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
16	16	0.720	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
17	17	0.619	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
18	18	0.537	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
19	19	0.469	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
20	20	0.413	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
21	21	0.365	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
22	22	0.323	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
23	23	0.287	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
24	24	0.254	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
25	25	0.224	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
26	26	0.197	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
27	27	0.174	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
28	28	0.155	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
29	29	0.139	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
30	30	0.125	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
31	31	0.113	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
32	32	0.102	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
33	33	0.093	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
34	34	0.085	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
35	35	0.078	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
36	36	0.072	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
37	37	0.066	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
38	38	0.061	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
39	39	0.056	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
40	40	0.052	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
41	41	0.048	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
42	42	0.044	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
43	43	0.041	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
44	44	0.038	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
45	45	0.035	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
46	46	0.033	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
47	47	0.031	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
48	48	0.029	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
49	49	0.027	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
50	50	0.026	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00

Table 4.21 Parameters at 3.50 microns

Alt. (km)	h	Rayleigh atten. coeff. (km ⁻¹)	Rayleigh optical thick. (0-h)	Rayleigh optical thick. (h-∞)	Aerosol atten. coeff. (km ⁻¹)	Aerosol optical thick. (0-h)	Aerosol optical thick. (h-∞)	Ozone absorp. coeff. (km ⁻¹)	Ozone optical thick. (0-h)	Ozone optical thick. (h-∞)	Ext. coeff. (km ⁻¹)	Ext. optical thick. (0-h)	Ext. optical thick. (h-∞)
0	0	6.929	0.00	0.00	7.00	0.00	0.00	0.00	0.00	0.00	7.00	0.00	0.00
1	1	6.137	0.00	0.00	3.06	0.00	0.00	0.00	0.00	0.00	3.06	0.00	0.00
2	2	5.511	0.00	0.00	1.53	0.00	0.00	0.00	0.00	0.00	1.53	0.00	0.00
3	3	5.059	0.00	0.00	0.82	0.00	0.00	0.00	0.00	0.00	0.82	0.00	0.00
4	4	4.533	0.00	0.00	0.45	0.00	0.00	0.00	0.00	0.00	0.45	0.00	0.00
5	5	4.105	0.00	0.00	0.25	0.00	0.00	0.00	0.00	0.00	0.25	0.00	0.00
6	6	3.520	0.00	0.00	0.15	0.00	0.00	0.00	0.00	0.00	0.15	0.00	0.00
7	7	3.287	0.00	0.00	0.09	0.00	0.00	0.00	0.00	0.00	0.09	0.00	0.00
8	8	2.931	0.00	0.00	0.05	0.00	0.00	0.00	0.00	0.00	0.05	0.00	0.00
9	9	2.592	0.00	0.00	0.03	0.00	0.00	0.00	0.00	0.00	0.03	0.00	0.00
10	10	2.335	0.00	0.00	0.02	0.00	0.00	0.00	0.00	0.00	0.02	0.00	0.00
11	11	2.034	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
12	12	1.739	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
13	13	1.480	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
14	14	1.270	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
15	15	1.095	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
16	16	0.931	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
17	17	0.793	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
18	18	0.678	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
19	19	0.587	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
20	20	0.521	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
21	21	0.453	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
22	22	0.390	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
23	23	0.335	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
24	24	0.287	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
25	25	0.245	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
26	26	0.209	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
27	27	0.178	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
28	28	0.150	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
29	29	0.125	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
30	30	0.102	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
31	31	0.084	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
32	32	0.070	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
33	33	0.059	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
34	34	0.050	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
35	35	0.043	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
36	36	0.037	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
37	37	0.032	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
38	38	0.028	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
39	39	0.024	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
40	40	0.021	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
41	41	0.018	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
42	42	0.016	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
43	43	0.014	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
44	44	0.012	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
45	45	0.010	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
46	46	0.009	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
47	47	0.008	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
48	48	0.007	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
49	49	0.006	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
50	50	0.005	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00

Table 4.22 Parameters at 4.00 microns

Alt. (km)	h	Rayleigh atten. coeff. (km ⁻¹)	Rayleigh optical thick. (0-h)	Rayleigh optical thick. (h-∞)	Aerosol atten. coeff. (km ⁻¹)	Aerosol optical thick. (0-h)	Aerosol optical thick. (h-∞)	Ozone absorp. coeff. (km ⁻¹)	Ozone optical thick. (0-h)	Ozone optical thick. (h-∞)	Ext. coeff. (km ⁻¹)	Ext. optical thick. (0-h)	Ext. optical thick. (h-∞)
0	0	4.002 -5	.000	.000	5.50 -2	.000	.000	0	.000	.000	6.50 -2	.000	.000
1	1	3.532 -5	.000	.000	2.77 -2	.045	.054	0	.000	.000	2.77 -2	.045	.054
2	2	3.283 -5	.000	.000	1.20 -2	.065	.094	0	.000	.000	1.20 -2	.065	.094
3	3	2.971 -5	.000	.000	5.02 -3	.074	.026	0	.000	.000	5.02 -3	.074	.026
4	4	2.677 -5	.000	.000	2.50 -3	.078	.022	0	.000	.000	2.50 -3	.078	.022
5	5	2.455 -5	.000	.000	2.00 -3	.080	.020	0	.000	.000	2.00 -3	.080	.020
6	6	2.157 -5	.000	.000	1.41 -3	.082	.018	0	.000	.000	1.41 -3	.082	.018
7	7	1.923 -5	.000	.000	1.31 -3	.083	.017	0	.000	.000	1.31 -3	.083	.017
8	8	1.713 -5	.000	.000	1.35 -3	.084	.015	0	.000	.000	1.35 -3	.084	.015
9	9	1.528 -5	.000	.000	1.50 -3	.085	.014	0	.000	.000	1.50 -3	.085	.014
10	10	1.351 -5	.000	.000	1.25 -3	.087	.013	0	.000	.000	1.25 -3	.087	.013
11	11	1.192 -5	.000	.000	1.18 -3	.088	.012	0	.000	.000	1.18 -3	.088	.012
12	12	1.013 -5	.000	.000	1.24 -3	.089	.010	0	.000	.000	1.24 -3	.089	.010
13	13	8.710 -7	.000	.000	1.15 -3	.090	.009	0	.000	.000	1.15 -3	.091	.009
14	14	7.445 -7	.000	.000	1.12 -3	.092	.008	0	.000	.000	1.12 -3	.092	.008
15	15	6.393 -7	.000	.000	1.06 -3	.093	.007	0	.000	.000	1.06 -3	.093	.007
16	16	5.433 -7	.000	.000	1.00 -3	.094	.006	0	.000	.000	1.01 -3	.094	.006
17	17	4.563 -7	.000	.000	9.35 -7	.095	.005	0	.000	.000	9.35 -7	.095	.005
18	18	3.974 -7	.000	.000	9.01 -7	.096	.004	0	.000	.000	9.61 -7	.096	.004
19	19	3.393 -7	.000	.000	8.09 -7	.097	.003	0	.000	.000	8.10 -7	.097	.003
20	20	2.905 -7	.000	.000	5.34 -7	.097	.002	0	.000	.000	5.34 -7	.097	.002
21	21	2.474 -7	.000	.000	4.34 -7	.096	.002	0	.000	.000	4.31 -7	.098	.002
22	22	2.108 -7	.000	.000	3.24 -7	.098	.001	0	.000	.000	3.24 -7	.098	.001
23	23	1.797 -7	.000	.000	2.43 -7	.098	.001	0	.000	.000	2.48 -7	.099	.001
24	24	1.534 -7	.000	.000	1.97 -7	.099	.001	0	.000	.000	1.97 -7	.099	.001
25	25	1.310 -7	.000	.000	1.55 -7	.099	.001	0	.000	.000	1.60 -7	.099	.001
26	26	1.113 -7	.000	.000	1.44 -7	.099	.001	0	.000	.000	1.44 -7	.099	.001
27	27	9.572 -8	.000	.000	1.10 -7	.099	.000	0	.000	.000	1.11 -7	.099	.000
28	28	8.193 -8	.000	.000	9.45 -8	.095	.000	0	.000	.000	8.45 -8	.099	.000
29	29	7.017 -8	.000	.000	6.50 -8	.099	.000	0	.000	.000	6.51 -8	.099	.000
30	30	6.015 -8	.000	.000	4.35 -8	.099	.000	0	.000	.000	4.33 -8	.099	.000
31	31	5.134 -8	.000	.000	3.81 -8	.099	.000	0	.000	.000	3.81 -8	.099	.000
32	32	4.429 -8	.000	.000	2.91 -8	.099	.000	0	.000	.000	2.92 -8	.100	.000
33	33	3.731 -8	.000	.000	2.23 -8	.100	.000	0	.000	.000	2.24 -8	.100	.000
34	34	3.240 -8	.000	.000	1.71 -8	.100	.000	0	.000	.000	1.71 -8	.100	.000
35	35	2.755 -8	.000	.000	1.51 -8	.100	.000	0	.000	.000	1.51 -8	.100	.000
36	36	2.371 -8	.000	.000	1.00 -8	.100	.000	0	.000	.000	1.01 -8	.100	.000
37	37	2.037 -8	.000	.000	7.70 -8	.100	.000	0	.000	.000	7.72 -8	.100	.000
38	38	1.753 -8	.000	.000	5.30 -8	.100	.000	0	.000	.000	5.32 -8	.100	.000
39	39	1.512 -8	.000	.000	4.51 -8	.100	.000	0	.000	.000	4.52 -8	.100	.000
40	40	1.305 -8	.000	.000	3.45 -8	.100	.000	0	.000	.000	3.47 -8	.100	.000
41	41	1.123 -8	.000	.000	2.55 -8	.100	.000	0	.000	.000	2.55 -8	.100	.000
42	42	9.784 -9	.000	.000	2.03 -8	.100	.000	0	.000	.000	2.04 -8	.100	.000
43	43	8.471 -9	.000	.000	1.55 -8	.100	.000	0	.000	.000	1.56 -8	.100	.000
44	44	7.360 -9	.000	.000	1.16 -8	.100	.000	0	.000	.000	1.20 -8	.100	.000
45	45	6.424 -9	.000	.000	9.07 -9	.100	.000	0	.000	.000	9.16 -9	.100	.000
46	46	5.700 -9	.000	.000	6.94 -9	.100	.000	0	.000	.000	7.03 -9	.100	.000
47	47	4.889 -9	.000	.000	5.34 -9	.100	.000	0	.000	.000	5.43 -9	.100	.000
48	48	4.202 -9	.000	.000	4.11 -9	.100	.000	0	.000	.000	4.15 -9	.100	.000
49	49	3.733 -9	.000	.000	3.13 -9	.100	.000	0	.000	.000	3.17 -9	.100	.000
50	50	3.355 -9	.000	.000	2.40 -9	.100	.000	0	.000	.000	2.43 -9	.100	.000

Acknowledgments

The author would like to acknowledge the helpful review provided by R.W. Fenn, R. Penndorf, and F. Volz. Appreciation is extended also to R. Wexler and D. Chang for their discussions pertaining to meteorological aspects and to R. Hoffman and J. Fusco for their participation with computer programming.

References

- Baum, W. A. and Dunkelman, L. (1955) Horizontal attenuation of ultraviolet light by the lower atmosphere, J. Opt. Soc. Am. 45:166.
- Bigg, E. K. (1964) Atmospheric stratification revealed by twilight scattering, Tellus, 16:77-83.
- Bullrich, K. (1964) Scattered radiation in the atmosphere and the natural aerosol, from Adv. in Geophysics, 10:101-257, H. E. Landsberg and J. E. Mieghem, Editors, Academic Press, N. Y.
- Clemesha, B. R., Kent, G. S., and Wright, R. W. (1967) A laser radar for atmospheric studies, J. Appl. Meteorol. 6:386-395.
- Collis, R. T. H. and Ligda, M. G. H. (1966) Note on Lidar observations of particulate matter in the stratosphere, J. Atmos. Sci. 23:255-257.
- Crosby, P. and Koerber, B. W. (1962) Scattering of light in the lower atmosphere, J. Opt. Soc. Am. 53:358-361.
- Curcio, J. A. and Durbin, K. A. (1959) Atmospheric Transmission in the Visible Region, NRL Rpt 5368, U.S. Naval Research Laboratory, Washington, D. C.
- Curcio, J. S., Knestrick, G. L., and Cosden, T. H. (1961) Atmospheric Scattering in the Visible and Infrared, NRL Rpt 5567, U.S. Naval Research Laboratory, Washington, D. C.
- Driving, A. Y. (1966) IZV. Atmospheric and oceanic physics, Vol. 2, No. 10, pp. 1046-1054 (U.D.C. 551.593.5:629.195).
- Dunkelman, L. (1952) Horizontal Attenuation of Ultraviolet and Visible Light by the Lower Atmosphere, NRL Rpt No. 4031, U.S. Naval Research Laboratory, Washington, D. C.
- Edlén, B. (1953) The dispersion of standard air, J. Opt. Soc. Am. 43:339.
- Elterman, L. (1964) Atmospheric Attenuation Model, 1964, in the Ultraviolet, Visible, and Infrared Regions for Altitudes to 50 km, Report AF-CRL-64-740, AF-CRL, Bedford, Mass.

References

- Elterman, L. (1966a) Aerosol measurements in the troposphere and stratosphere, Appl. Opt. 5: 1769.
- Elterman, L. (1966b) An Atlas of Aerosol Attenuation and Extinction Profiles for the Troposphere and Stratosphere, Report AFCRL-66-828, AFCRL, Bedford, Mass.
- Fenn, R.W. (1964) Aerosol-Verteilungen und atmospharisches Streulicht, Beitrage zur Physik der Atmosphere, 34(No.2):69.
- Fekhtistov, K.P. (1965) Some results of optical observations from a Voskhod spacecraft, in: G.A. Skuridin, et al., eds. Issledovaniia kosmicheskogo prostranstva (Investigations of Cosmic Space). Moscow, Izd-vo "Nauka", pp. 62-64.
- Foitzik, L. (1965) The spectral extinction of the atmospheric aerosol by Mie particles with different Gaussian distributions, Gerlands Beitrage zur Geophysik 73, Heft 3, 199.
- Friend, J.R. (1965) Properties of the Stratospheric Aerosol, Isotopes, Inc., Report for contract DA-49-146-XZ-079 Defense Atomic Support Agency (U) 2 Nov.
- Grams, G. and Flocco, G. (1967) Stratospheric aerosol layer during 1964 and 1965, J. Geophys. Res. 72:3523-3542.
- Gucker, F.T. and Basu, S. (1953) Right-angle Molecular Light Scattering from Gases, Sci. Rpt No. 1, Contract AF19(122)-400, U. of Indiana.
- Junge, C.E., Chagnon, C.W., and Manson, J.E. (1961) Stratospheric aerosols, J. Meteorol. 18:81.
- Junge, C.E. (1963) Air Chemistry and Radioactivity, Academic Press, N.Y.
- Knestrick, G.L., Cosden, T.H., and Curcio, J.A. (1961) Atmospheric Attenuation Coefficients in the Visible and Infrared, NRL Rpt 5648, U.S. Naval Research Laboratory, Washington, D.C.
- Kondratiev, K. Ya., Nicolsky, G.A., Badinov, I. Ya., and Andreev, S.D. (1967) Direct solar radiation up to 30 km and stratification of attenuation components in the stratosphere, Appl. Opt. 6:197.
- London, J., Ooyama, K. and Prabhakara, C. (1962) New York U. Final Rpt, Contract AF19(604)-5492, AFCRL, Bedford, Mass.
- Mateer, C.L., Dave, J.V., Dunkelmann, L., and Evans, D.C. (1967) Evidence of an Upper Stratospheric Dust Layer in a Satellite Twilight Color Photograph, Report X-613-67-533, Goddard Space Flight Center, Greenbelt, Maryland.
- Meinel, A.B. and Meinel, M.F. (1964) Height of the glow stratum from the eruption of Agung on Bali, Nature, 201:657-658.
- Miller, D.E. (1967) Stratospheric attenuation in the near ultraviolet, Proc. Roy. Soc. (London) A301:57.
- Mossop, S.C. (1964) Volcanic particles collected at an altitude of 20 km, Nature, 203:824.
- Nauwink, G., Jr. and Eddy, J.A. (1964) Light scattering by particles in the upper atmosphere, J. Atmos. Sci., 21:35-60.

References

- Penndorf, R. (1954) The Vertical Distribution of Mie Particles in the Troposphere, Geophysics Research Paper No. 25, AFCRL, Bedford, Mass.
- Penndorf, R. (1957) Tables of refractive index for standard air and the Rayleigh scattering coefficient for the spectral region between 0.2 and 20.0μ and their application to atmospheric optics, J. Opt. Soc. Am. 47:176.
- Rosen, J. (1968) Simultaneous dust and ozone soundings over North and Central America, J. Geophys. Res. 73:479.
- Rozenberg, G.V., Ed. (1960) Prozhektornyi luch v atmosfere (Searchlight beams in the atmosphere), by I.U.S. Georgievskii, et al., Moscow, Izd-vo AN SSSR.
- Rozenberg, G.V. (1965) Sumerki, Moscow, Fizmatgiz, 1963 (Engl. transl.: Twilight, New York, Consultants Bureau).
- Rozenberg, G.V. (1966) Paper presented at the International Conference on the Investigation of Noctilucent Clouds, Tallin.
- Sandomirskii, A.B., Al'tovskaya, N.P. and Trifonova, G.I. (1964) The seasonal variation of brightness at heights up to 17.5 km, Izvestia AN SSSR, Ser. Geofiz. No. 7:1121-1127.
- Spankuch, D. (1967) Brightness measurements with a vertical searchlight beam for the determination of the vertical turbidity stratification in the troposphere, Beitrage zur Physik der Atmosphere, 40, 1/2, 95/117.
- Stergis, C.G. (1966) Rayleigh Scattering in the Upper Atmosphere, Report AFCRL 66-287, AFCRL, Bedford, Mass.
- Vigroux, E. (1953) Contributions a l'etude experimentale de l'absorption de l'ozone, Ann. Phys. (Paris) 8:709.
- Volz, F.E. (1965) Note on the global variation of stratospheric turbidity since the eruption of Agung Volcano, Tellus 17:513-515.
- Volz, F.E. and Goody, R.M. (1962) The intensity of the twilight and upper atmospheric dust, J. Atmos. Sci. 19:385-426.
- Volz, F. (1968) Twilight and stratospheric dust before and after the Agung eruption, paper in preparation.
- Waldram, J.M. (1945) Measurements of the photometric properties of the upper atmosphere, J. Meteorol. 71:319-336.
- U.S. Standard Atmosphere 1962, U.S. Govt. Printing Office, Washington 25, D.C.

Unclassified
Security Classification

DOCUMENT CONTROL DATA - R&D		
(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)		
1. ORIGINATING ACTIVITY (Corporate author) Air Force Cambridge Research Laboratories (CRO) L. G. Hanscom Field Bedford, Massachusetts 01730		2a. REPORT SECURITY CLASSIFICATION Unclassified
		2b. GROUP
3. REPORT TITLE UV, VISIBLE, AND IR ATTENUATION FOR ALTITUDES TO 50 KM, 1968		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Scientific. Interim.		
5. AUTHOR(S) (First name, middle initial, last name) Louis Elterman		
6. REPORT DATE April 1968	7a. TOTAL NO. OF PAGES 56	7b. NO. OF REFS 45
8a. CONTRACT OR GRANT NO.		8b. ORIGINATOR'S REPORT NUMBER(S) AFCRL-68-0153
a. PROJECT, TASK, WORK UNIT NOS. 7670-04-01	b. DOD ELEMENT 6240539F	9a. OTHER REPORT NO(S) (Any other numbers that may be assigned this report) ERP No. 285
c. DOD SUBELEMENT 681000		
10. DISTRIBUTION STATEMENT 1 - Distribution of this document is unlimited. It may be released to the Clearinghouse, Department of Commerce, for sale to the general public.		
11. SUPPLEMENTARY NOTES TECH, OTHER		12. SPONSORING MILITARY ACTIVITY Air Force Cambridge Research Laboratories (CRO) L. G. Hanscom Field Bedford, Massachusetts 01730
13. ABSTRACT An atmospheric attenuation model for the ultraviolet, visible, and infrared was developed in 1964, based on scattering (molecules and aerosols) and ozone absorption. Since then more measurements have been made and our knowledge of aerosol attenuation has widened. These circumstances result in attenuation model changes which are relatively unimportant for most exploratory calculations. They can be significant, however, for long slant-path high-altitude applications entailing large zenith angles, factors which characterize, for example, the measurement geometries of rockets and satellites. Accordingly, a revision of the 1964 Attenuation Model is warranted. In this paper the optical parameters are computed spectrally and with altitude as follows: (1) pure air attenuation parameters are determined by utilizing Rayleigh scattering cross sections with molecular number densities from the standard atmosphere; (2) ozone absorption parameters are derived based on Vigroux's coefficients applied to a representative atmospheric ozone distribution; (3) seven sets of aerosol measurements are compared and a profile of aerosol attenuation coefficients vs altitude is developed. Attenuation coefficients and optical thickness due to molecular, aerosol, and ozone attenuation are computed and tabulated individually so that the influence of each can be compared. The newly derived tabulations permit various exploratory calculations, including horizontal, vertical, and slant-path transmission at kilometer intervals to an altitude of 50 km, individually for each attenuating component or for overall atmospheric extinction (molecular + ozone + aerosol).		

DD FORM 1473
1 NOV 65

Unclassified
Security Classification

Unclassified
Security Classification

16.	KEY WORDS	LINK A		LINK B		LINK C	
		ROLE	WT	ROLE	WT	ROLE	WT
	UV atmospheric transmission Visible atmospheric transmission IR atmospheric transmission Aerosol atmospheric attenuation Transmission in troposphere and stratosphere Aerosol attenuation in troposphere and stratosphere Model atmosphere Light scattering						

Unclassified
Security Classification